

DRA

(NASA-CR-124004) CORRELATION SIGNATURES  
OF WET SOILS AND SNOWS Final Report,  
22 Mar. 1971 - 22 Sep. 1972 (IIT  
Research Inst.) 180 p HC \$11.00

N74-11214

Unclas  
22587

CSCL 08M G3/13

IITRI

UNCLASSIFIED

Security Classification

## DOCUMENT CONTROL DATA - R &amp; D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) IIT Research Institute 10 West 35th Street Chicago, Illinois 60616		2a. REPORT SECURITY CLASSIFICATION	
		2b. GROUP	
3. REPORT TITLE CORRELATION SIGNATURES OF WET SOILS AND SNOWS			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Final Report			
5. AUTHOR(S) (First name, middle initial, last name) M. R. Phillips			
6. REPORT DATE October 1972	7a. TOTAL NO. OF PAGES 173	7b. NO. OF REFS	
8a. CONTRACT OR GRANT NO. Contract NAS8-26797	9a. ORIGINATOR'S REPORT NUMBER(S) J6243-6		
b. PROJECT NO.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)		
c.			
d.			
10. DISTRIBUTION STATEMENT			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY NASA George C. Marshall Space Flight Ctr Marshall Space Flight Ctr, Alabama	
13. ABSTRACT  SUMMARY  During the past several months and since the inception of the Flight Data Statistics Office, a growing trend to analyze and process Earth Resources Flight Data has prevailed. In view of the growing interest at Marshall Space Flight Center to organize and establish capabilities to perform research studies in this area, endeavors in the areas of interpretation, analysis, and development of algorithms have provided the necessary computational programming tools for data processing and data handling and analysis. Algorithms that have been developed thus far, are adequate and have been proven successful for several preliminary and fundamental applications such as software interfacing capabilities, probability distributions, grey level print plotting, contour plotting, isometric data displays, joint probability distributions, boundary mapping, channel registration and ground scene classification. This report is written in two sections. Section I consists of the algorithms that have been developed individually under the existing contract and section II is a description of an Earth Resources Flight Data Processor, (ERFDP), which handles and processes earth resources data under a users control.			

DD FORM 1473

REPLACES DD FORM 1473, 1 JAN 64, WHICH IS OBSOLETE FOR ARMY USE.

UNCLASSIFIED

Security Classification

I

Engineering Mechanics Division  
IIT Research Institute  
10 West 35th Street  
Chicago, Illinois 60616

CORRELATION SIGNATURES OF WET SOILS  
AND SNOWS

IITRI Final Report J6243-6  
Contract NAS8-26797  
Period 22 March 1971 to 22 September 1972

M. R. Phillips

Prepared for  
George C. Marshall Space Flight Center  
Marshall Space Flight Center, Alabama 35812

CORRELATION SIGNATURES OF WET SOILS AND SNOWS

M. R. Phillips

-      Engineering Mechanics Division  
         IIT Research Institute  
         10 West 35th Street  
         Chicago, Illinois 60616

-      Final Report  
         Contract NAS8-26797  
Period 22 March 1971 to 22 September 1972  
         October 1972

-      Prepared for  
         George C. Marshall Space Flight Center  
Marshall Space Flight Center, Alabama 35812

## FOREWORD

This final technical report, entitled "Correlation Signatures of Wet Soils and Snows", presents the results of 18 months programming and algorithm development under the auspices of the National Aeronautics and Space Administration (NASA), with Mr. Robert Jayroe acting COR. This work was performed under contract NAS8-26797 (IITRI Project J6243).

## CONTENTS

	<u>Page</u>
SUMMARY	1
SECTION I INTRODUCTION	1
1. Probability Distribution	2
A. Computer Program	2
B. Data Problem Parameters	4
2. Grey Level Mapping	4
A. Computer Program	6
B. Data Problem Parameters	6
3. Contour Plotting	7
A. Computer Program	8
B. Data Problem Parameters	11
4. Isometric Displays	11
A. Computer Program	12
B. Data Problem Parameters	12
5. Dynamic Joint Probability Distribution	14
6. Joint Probability Density Function	19
A. Computer Program	20
B. Core Storage Image	20
C. Output Display	23
D. Data Problem Parameters	23
7. Boundary Mapping	25
A. Data Problem Parameters	39
8. Channel Alignment	40
A. Computer Program	42
B. Data Problem Parameters	42
C. Program Flow Chart	43
9. Channel Registration	46
A. Computer Program	47
B. Data Problem Parameters	47
C. Program Flow Chart	48
10. Spectral Discrimination	51

## CONTENTS (concl)

	<u>Page</u>
SECTION II INTRODUCTION	53
1. Earth Resources Flight Data Processor	56
2. Module One	59
A. Data Problem Parameters Example Setup	59
B. Input Tapes	59
C. Output Tapes	59
D. Program Flow Chart	60
3. Module Two	63
A. Data Problem Parameters Example Setup	63
B. Input Tapes	64
C. Output Tapes	64
D. Program Flow Chart	65
4. Module Three	70
A. Data Problem Parameters Example Setup	70
B. Input Tapes	71
C. Output Tapes	71
D. Program Flow Chart	72
5. Module Four	77
A. Data Problem Parameters Example Setup	77
B. Input Tapes	78
C. Output Tapes	78
D. Program Flow Chart	79
6. Module Five	85
A. Data Problem Parameters Example Setup	85
B. Input Tapes	86
C. Output Tapes	86
D. Program Flow Chart	87
7. Module Six	95
A. Data Problem Parameters Example Setup	95
B. Input Tapes	96
C. Output Tapes	96
D. Program Flow Chart	97
8. Module Seven	102
A. Data Problem Parameters Input Example	103
B. Input Tapes	108
C. Output Tapes	108
D. Intermediate Tapes	108
E. Program Flow Chart	109
APPENDIX: COMPUTER PROGRAM LISTING	123

## ILLUSTRATIONS

	<u>Page</u>
1. Quantized Probability Distribution Curve	5
2. Boundary Contours (Purdue C1)	9
3. Boundary Determination Channels 4 of 12 (Purdue C1)	10
4. Flight Data Display	15
5. Flight Data Display	16
6. Flight Data Display	17
7. Flight Data Display	18
8. Data Arrays Before and After Vertical Sort	21
9. Core Storage Image	22
10. Core Storage Image	24
11. Isometric Display of Ground Scene	26
12. Area Configurations Produced by Four Adjacent Data Samples	27
13. Area Equations for Four Adjacent Data Samples	28
14. Flow Diagram of Decision Logic	29
15. Boundary Determination, Probability Distribution Channel 3	31
16. Boundary Determination, Probability Distribution Channel 12	32
17. Boundary Determination Channel 12 (Purdue C1)	34
18. Boundary Determination Channel 3 (Purdue C1)	35
19. Boundary Determination Channels 7 of 12 (Purdue C1)	36
20. Boundary Determination Channels 3 of 12 (Purdue C1)	37
21. Boundary Determination Channels 4 of 12 (Purdue C1)	38
22. Block Diagram Depicting Modular Structure	54



## ILLUSTRATIONS (concl)

	<u>Page</u>
23. Block Diagram ERFDP	55
24. Block Diagram ERFDP	57
25. Module Seven Output Example	104
26. Results of Sequential Merging and Classifying Process	105
27. Clustered Homogeneous Areas	106
28. Merged and Classified Homogeneous Areas	107
29. IBM 7094 Job Deck Setup	121
30. IBM 7094 Instruction Form 533	122

# CORRELATION SIGNATURES OF WET SOILS AND SNOWS

M. R. Phillips  
IIT Research Institute

## SUMMARY

During the past several months and since the inception of the Flight Data Statistics Office, a growing trend to analyze and process Earth Resources Flight Data has prevailed. In view of the growing interest at Marshall Space Flight Center to organize and establish capabilities to perform research studies in this area, endeavors in the areas of interpretation, analysis, and development of algorithms have provided the necessary computational programming tools for data processing and data handling and analysis. Algorithms that have been developed thus far, are adequate and have been proven successful for several preliminary and fundamental applications such as software interfacing capabilities, probability distributions, grey level print plotting, contour plotting, isometric data displays, joint probability distributions, boundary mapping, channel registration and ground scene classification. This report is written in two sections. Section I consists of the algorithms that have been developed individually under the existing contract and section II is a description of an Earth Resources Flight Data Processor, (ERFDP), which handles and processes earth resources data under a users control.

## SECTION I INTRODUCTION

In this section a description of each algorithm developed under the existing contract will be presented. The algorithms were developed as building blocks toward an automatic data processor for processing earth resources flight data. Each algorithm has been demonstrated to be compatible in an overall automatic processing environment. These algorithms were developed using an IBM 7094 computer with 32K available core storage.

## 1. PROBABILITY DISTRIBUTION

A probability density function was programmed, and the earth resources data processor which is available upon request as an option selection is included. This option gives a probability density function for any number of channels, not to exceed 12, of the multispectral data. This option is used when calculating the slicing intervals of the probability distribution to provide grey level mapping of any ground scene image. An estimate of the probability density function is obtained digitally by dividing the range of the data into a desired number of class intervals  $d_i$ . The probability of occurrence of a value  $X_i$  in the class interval is then given by

$$P_i(X) = N_i(X)/N,$$

where  $N_i(X)$  is the number of values that occur within the range of  $d_i < X \leq d_{i+1}$  and

$$N = \sum_{i=0}^{k-1} N_i$$

is the total size of the population where  $K$  = number of class intervals.

### A. Computer Program

The computer program calculates the probability density of any channel of a multispectral scanner consisting of 12 channels of data. The distribution table is then printed out for all channels requested, over all the data samples (see table I). The program also passes to the grey level module the probability distribution of each channel for grey level mapping.

TABLE I  
PROBABILITY DISTRIBUTION

AMPLITUDE	CH 1	CH 2	CH 3	CH 4	CH 5	CH 6	CH 7	CH 8	CH 9	CH 10	CH 11	CH 12
-1.5	0	0	0	0	0	0	0	0	0	0	0	0
-1.4	0	0	2	0	2	0	0	0	0	0	1	0
-1.3	0	0	3	0	0	0	0	0	0	0	0	0
-1.2	1	0	9	0	5	0	0	1	0	0	1	0
-1.1	0	0	21	0	7	0	0	0	1	1	8	0
-1.0	5	0	29	0	15	1	0	1	0	0	22	0
-.9	4	0	35	0	17	1	0	3	2	4	31	0
-.8	8	1	39	0	34	2	3	9	7	8	47	0
-.7	12	0	48	0	39	8	8	18	20	16	60	0
-.6	24	7	55	1	47	12	12	22	25	30	55	0
-.5	21	11	66	0	51	22	22	38	40	40	40	0
-.4	38	5	58	2	55	31	41	47	48	52	27	0
-.3	45	12	49	12	49	49	70	50	55	60	11	0
-.2	57	22	42	18	44	66	82	54	62	72	6	5
-.1	59	37	33	20	39	72	96	47	51	55	5	1
0	62	44	25	35	33	62	79	41	45	52	0	8
.1	58	48	19	30	25	40	62	35	39	31	1	16
.2	51	49	12	41	18	22	38	25	25	20	0	27
.3	47	56	6	54	7	12	12	17	16	15	0	32
.4	35	52	1	61	8	8	10	12	8	7	0	39
.5	25	40	0	55	2	2	7	8	5	3	0	47
.6	22	32	1	45	1	0	2	0	1	5	0	52
.7	8	24	0	40	0	1	1	2	0	1	0	65
.8	5	16	0	35	1	0	0	0	0	0	0	72
.9	7	8	0	28	0	0	0	0	0	0	0	58
1.0	3	7	0	20	0	0	0	0	0	0	0	46
1.1	1	1	0	12	0	0	0	0	0	0	0	39
1.2	0	0	0	7	0	0	0	0	0	0	0	22
1.3	1	1	0	0	0	0	0	0	0	0	0	7
1.4	0	0	0	1	0	0	0	0	0	0	0	1
1.5	0	0	0	0	0	0	0	0	0	0	0	0

NUMBER OF OCCURRENCES

## B. Data Problem Parameters

NCH	Number of channels or spectral bands on input tape
NSPS	Number of samples per record or resolution elements across one scan
NSCANS	Number of scans to process
NSTART	Starting resolution element
NSTOP	Stopping resolution element
NBTLG	Bit length of input data word
MODE	Signifying FORTRAN or non-FORTRAN input tape
ITYPE	Type of input data; Floating point or fixed point
MSFC	MSFC scanner format option
LTN	Logical unit to load input tape
NSKIP	Number of initial data records to skip before processing
NCRE	Data incrementation
XMAX	Maximum value in data set
XMIN	Minimum value in data set
NOCHS	Number of channels to calculate probability density function
NWHICH	Channel selection for probability distribution calculation

## 2. GREY LEVEL MAPPING

In order to preview earth resources data and obtain quick-look information, a grey level mapping program was written to include in the ERFDP. This gives a pictorial display of the ground scene image quantized to 10 different levels. Characters are selected to represent varying shades of grey. The levels are calculated by slicing the probability distribution table of selected channels into 10 separate cells (see Figure 1). The number of occurrences in each cell is equally distributed over the probability distribution. This is done by calculating equal areas for each cell using the trapezoidal rule method. Each of the 10 areas would represent one cell of the probability distribution. Each resolution element is compared with all the cells, and the cell in which it falls is assigned the respective alphanumeric character.

Ten Equal Area Intervals




Figure 1 Quantized Probability Distribution Curve

### A. Computer Program

The computer program was written as a module to be included in the ERFDP. The logic provides communication with the probability distribution program, since information calculated in that module is used in grey level mapping. The data are input to the program module and each resolution element input to the module is compared with each cell until it falls within the quantized level of that cell. Each resolution element,  $x_i$ , is examined such that

$$\text{SLICE } (j-1) < x_i \leq \text{SLICE } (j) \\ \text{where } j = 1, 2, 3 \dots, 11.$$

After the data point,  $x_i$  has been quantized by this method, it is replaced by its representative alphanumeric character and plotted or printed. The plotting is output to the Stromberg-Carlson 4020 recorder for display.

If automatic quantization is not desired, the program provides an option where the user can input quantized levels as a table if other methods are desired (reference ERFDP users manual, section II of this report).

### B. Data Problem Parameters

NCH	Number of channels on input tape
NSPS	Number of samples per record or scan
NSCANS	Number of scans to process
NSKIP	Number of scans to skip before processing
NSTART	Starting sample number in the scan
NSTOP	Stopping sample number in the scan
ITERM	Number of passes to make processing 120 samples each pass
N	Number of quantized levels plus one
ICHAN	Selected channel used in grey level mapping
IPRT	Option to print grey level

IPLT	Option to plot grey level
INCX	Increment in x direction for each sample (rasters)
INCY	Increment in y direction for each sample (rasters)
NSTX	Starting x coordinates or plot frame
NSTY	Starting y coordinates on plot frame
NBTLG	Bit length of input data words
MODE	Signifies FORTRAN or non-FORTRAN
ITYPE	Type of input data; Floating point or fixed point
MSFC	MSFC scanner format option
NCRE	Data increment
LTN	Logical tape unit to load input data
IOPT	Option to select automatic quantization or input quantized table

### 3. CONTOUR PLOTTING

In the analysis and interpretation of earth resources data, a useful tool is means of locating and outlining borders of ground scene images and also plot the snow pack temperature profiles recorded by an electronic scanner. A computer program was written to generate line plots, which is a line connecting points of boundaries, specified altitudes, temperatures, etc., providing a graphical display of contour levels or borders of ground scene images.

The data array to be plotted consists of the input data array only. These data points are ordered in an x y coordinate system. Four adjacent data points and their coordinates are examined to determine if a specified value intersects any of these four points. If an intersection occurs, these coordinates are converted to plotting raster counts, and two points are flagged. One point being coordinates of the entry point to the four adjacent data points and the other being the coordinates of the exit point of the four adjacent data points. If the intersection of a specified level continues to the next four successive



adjacent data points, then the coordinates of the exit point become the coordinates of the entry point of the next four adjacent data points. A search continues for the coordinates of the exit point and this procedure continues until the data set is exhausted. Lines are drawn connecting the points, reflecting continuity of the specified level. If the entry and exit point of successive four adjacent data points exist, then a line connecting these points is continuous. Otherwise, there exists a discontinuity and the points will not be connected. Continuous lines of multiple levels can be drawn reflecting contours of altitude, temperatures, and homogeneous area boundaries.

#### A. Computer Program

The computer program was written as a module to be included in the ERFDP and was designed to contour data sets of infinite lengths. However, only 2500 data points reside in the computer at one time because of the physical storage limits. Since only one block of data is processed at one time, the program automatically reloads blocks of data and abuts each block to provide a continuous plot of contours.

In Figure 2 contours of boundaries were plotted of the first 120 scans of field C1 from the Purdue data set. The data were blocked such that contours of 1776 resolution elements were plotted which covered eight scans. Each resolution element covered eight rasters on the plot frame, therefore each block abutted together occupies 64 rasters. After the abutment process, the boundary contours appear continuous. The boundaries that were contoured are shown in Figure 3. The boundary contours are elongated slightly due to scaling on the plot frame.

SCAN 1-120

RESOLUTION ELEMENT 1-222




Figure 2 Boundary Contours (Purdue C1)

SCAN 1-120

RESOLUTION ELEMENT 1-222




Figure 3 Boundary Determination Channels 4 of 12 (Purdue C1)

## B. Data Problem Parameters

NCH	Number of channels on input tape
NSPS	Number of samples in a scan
IRW	Logical tape units to load input data
NCHAN	Channel number
NSNCRE	Number of scans to increment
NPCRE	Number of samples to increment
NPTSL	Lower starting point
NPTSU	Upper stopping point
NOTLG	Bit length of input data word
ITYPE	Type data on input tape; Floating point or fixed point
MSFC	MSFC scanner format option
NSKIP	Number of records to skip
MAXSCN	Total number of scans to process
NSECT	Number of sections to process
MSZX	Data block size in x (samples)
MSZY	Data block size in y (scans)
BLK	Plot frame block size in rasters
FHINC	Contour level increment
ZMIN	Minimum contour level
ZMAX	Maximum contour level
LAB	Label interval

## 4. ISOMETRIC DISPLAYS

On occasion it has become necessary to preview the raw data and to determine the physical appearance to better understand the behavior of data collected from various ground scenes and from different types of sensors. For this purpose an isometric program was written to produce a two-dimensional projection of a three-dimensional graph of the raw data amplitude versus the x and y ground scene coordinates.

### A. Computer Program

Program Isometric will handle any FORTRAN IV formatted tape with up to 12 channels of data. Only one channel is plotted per computer pass and the channel selection is based upon an input parameter.

The program was developed to produce two-dimensional data projections of ground cover scenes where data are gathered by sensors aboard an aircraft. The data collected across the flight line represent resolution elements, and the data collected along the flight line represent scans. Any NXM array can be displayed where N is the position in an array and M is the value to be displayed. The program does not require large amounts of core storage since it performs a continuous operation on the NXM array which is refilled before each operation.

The Stromberg-Carlson 4020 frame reference coordinates are altered after each operation for proper scaling based on the input parameters provided by the user. These parameters also control the density of the points plotted and the angle of rotation desired for display. Multiple plot frames are generated as necessary to display all the input data. To provide frame abutment for a continuous plot, the last row of each frame and the last sample of each row is stored and repeated on the next frame.

### B. Data Problem Parameters

NCH	Total number of channels per resolution element on input tape
NSPS	Total number of resolution elements per channel across the ground scene
IRW	Logical tape number for input data
NCHAN	Number of the channel that isometrics are to be displayed
NSNCRE	Number of scans to increment along the flight line; This provides an option to use every scan line, every other scan line, etc.

NPCRE	Number of resolution elements to increment going across the flight line; If every resolution element is not desired, resolution elements can be skipped.
NPTSL	Starting resolution element number for the isometric
NPTSU	Stopping resolution element number for the isometric
MAXSON	Total number of scans along the flight to display
YMIN	The minimum value of the input data used for calculating scale factors for plotting the y axis
YMAX	The maximum value of the input data used also for calculating scale factors for plotting the y axis
NBLSZX	Stromberg-Carlson 4020 reference frame coordinate increment in the x direction
NBLSZY	Stromberg-Carlson 4020 reference frame coordinate increment in the y direction in raster counts (normal range 6 to 12) NBLSZX and NBLSZY are used to determine the degree of rotation of the isometric.
NSECT	Number of passes through the data necessary to display the full-scan width; If NPTSL and NPTSU only cover a portion of the data then NSECT can be adjusted to cover all the data.  Example: If NPTSL = 1, NPTSU = 128 and NSPS = 256, then NSECT = 2 will cover resolution element 1 through 128 and resolution element 129 through 256.
NSMOV	Number of points in a moving mean span used in smoothing the input data; Set to zero if smoothing is not desired.
NDIREC	Direction of the rotation of the isometric; 1 = counterclockwise and -1 = clockwise rotation.

A portion of flight line C1 (Purdue data set) was used in the following examples. Every resolution element and every scan was used requiring two passes through the data. NSECT was set to 2, but only one section is shown here. NBSZX and NBSZY were set to 8 and 12 respectively and both counterclockwise and clockwise rotations were used.

Figure 4 shows scan lines 86-129 and resolution elements 1-111 of the total 222 elements of channel 8. NDIREC was set to -1 to rotate clockwise. Figure 5 shows channel 8 with only NDIREC changed to +1 to rotate counterclockwise. Figures 6 and 7 reflect identical isometrics using channel 2 of the same data.

## 5. DYNAMIC JOINT PROBABILITY DISTRIBUTION

Extensive data analysis of data on hand has revealed inadequacies in the current joint probability distribution program. The program was restrictive in that a fixed amount of square storage array allocation was required. This meant that, the greater the spread of the clusters of the joint probabilities or individual data pairs, the larger the square storage array required. This also required a screening of all the data to determine the ranges of data pairs. After determining the data ranges, the minimum square storage array required to display the joint probabilities became  $NXM$ , where  $N$  is the range between the minimum and maximum value of the  $X$  data in the joint pairs, and  $M$  is the range between the minimum and maximum value of the  $Y$  data in the joint pairs. As this clearly points out, this does not adapt itself favorably to data that is ill behaved and possessing widely spread data clusters or widely spread individual data pairs. Due to the physical limits of the computer storage, in numerous cases, a considerably amount of data was lost. This depended largely on the characteristics of the data and since the primary function of the program was to display the dependent characteristics of two data channels, this required rerunning the program and making adjustments to the limits. Therefore, the program became inadequate.

FLIGHT LINE C1  
SCANS 1-43  
RESOLUTION ELEMENTS 1-111  
ROTATED CLOCKWISE  
CHANNEL 8 0.58-0.62 (MICRONS)




Figure 4 Flight Data Display



FLIGHT LINE C1  
SCANS 1-43  
RESOLUTION ELEMENT 1-111  
ROTATED COUNTER-CLOCKWISE  
CHANNEL 8 0.58-0.62 (MICRONS)




Figure 5 Flight Data Display

FLIGHT LINE C1  
SCANS 1-43  
RESOLUTION ELEMENTS 1-111  
ROTATED CLOCKWISE  
CHANNEL 2 0.44-0.46 (MICRONS)




Figure 6 Flight Data Display

FLIGHT LINE C1  
SCAN NO. 1-43  
RESOLUTION ELEMENT 1-111  
ROTATED COUNTER-CLOCKWISE  
CHANNEL 2 0.44-0.46 (MICRONS)




Figure 7 Flight Data Display

A new technique has been employed, that adapts itself to data of any nature, particularly cluster data where the data clusters are tremendously scattered. The technique requires only as much storage as actually required by the number of different data pairs and the size of the data storage required is not dependent on the ranges of the data.

## 6. JOINT PROBABILITY DENSITY FUNCTION

A joint probability density function program is a necessary tool in the analysis of earth resources flight data. This program gives a preliminary insight to the commonality of occurrences observed from two time-series data traces.

For applications to feature extraction, the outputs of this program give insight to the distinctness of different features and the location of decision boundaries necessary to separate different features.

The joint probability distribution is calculated digitally by selecting a range  $[a, b]$  on both sets of data  $X, Y$  and dividing the range into  $K$  intervals. This gives

$$C = \frac{b-a}{K} = \text{scale factor}$$

To find the  $X$  and  $Y$  coordinate for each variable  $X$  and  $Y$  jointly, an indexing pointer is calculated for each value of  $X$  and  $Y$  by

$$I_x = \frac{(x_n - a)}{C} \quad \text{and} \quad I_y = \frac{(y_n - a)}{C}$$

An integer one is added to the coordinate  $p(I_x, I_y)$  for every value of  $X$  and  $Y$  in the interval  $[a, b]$ . The coordinate  $p(I_x, I_y)$  contains the total number of occurrences.

### A. Computer Program

Data points are paired (user option), given a class, and are stored in two single arrays, one for the X coordinates,  $NP_x$ , and one for the Y coordinates,  $NP_y$ . The number of data pairs that are common is accumulated in an array NKNT (i) identifying the class and the number of occurrences, i, of that class.

The first data pair read from the input tape, will be assigned class number 1 automatically. All subsequent data pairs read from the input tape, will be compared with all the individual data pairs that have been assigned a particular class. If no match is found during the comparison, a new class is created, using this data pair. There can be up to 4000 different classes of paired data points stored.

Once all the data pairs are classified, the data pairs are arranged and sorted such that the Y coordinates or vertical data are sorted in descending order and the X coordinates or horizontal data are sorted in ascending order. Data are rearranged in such a way that the largest spread between the minimum and maximum is displayed on the vertical axis, which is printed down the print paper. An example of the three data arrays containing the joint probability before and after the vertical sort is shown in Figure 8a and 8b.

### B. Core Storage Image

For any data configuration, the core storage image will appear as in Figure 9a. Projecting this onto an NXM storage array used in the conventional method, shows the wasted storage which is used to store blanks (or no occurrences). See Figure 9b. The conventional data storage method required for this example is  $6 \times 7$ , or 42 core storage locations. The present scheme requires only 21 core storage locations to display the above example. The advantage, also, is that only 21 core storage locations are necessary regardless of the scatter of the joint probabilities.

$NP_x(8)_1$	$NP_y(6)_1$	$NKNT(1)_1$
• $(6)_2$	• $(12)_2$	• $(6)_2$
• $(12)_3$	• $(8)_3$	• $(8)_3$
• $(8)_4$	• $(7)_4$	• $(12)_4$
$(2)_5$	$(7)_5$	$(8)_5$
$(14)_6$	$(5)_6$	$(7)_6$
$(2)_7$	$(3)_7$	$(6)_7$

a. Before Vertical Sort

$NP_x(6)_1$	$NP_y(12)_1$	$NKNT(6)_1$
• $(12)_2$	• $(8)_2$	• $(8)_2$
• $(8)_3$	• $(7)_3$	• $(12)_3$
• $(2)_4$	• $(7)_4$	• $(8)_4$
$(8)_5$	$(6)_5$	$(1)_5$
$(14)_6$	$(5)_6$	$(7)_6$
$(2)_7$	$(3)_7$	$(6)_7$

b. After Vertical Sort

Figure 8 Data Arrays Before and After Vertical Sort

$NP_x(4)_1$	$NP_y(7)_1$	$NKNT(6)_1$
• $(3)_2$	• $(6)_2$	• $(8)_2$
• $(6)_3$	• $(5)_3$	• $(12)_3$
• $(2)_4$	• $(5)_4$	• $(8)_4$
$(6)_5$	$(3)_5$	$(1)_5$
$(5)_6$	$(3)_6$	$(7)_6$
$(1)_7$	$(2)_7$	$(6)_7$

a. Core Storage Configuration

•	•	•	6	•	•
•	•	8	•	•	•
•	8	•	•	•	12
•	•	•	•	•	•
•	•	•	•	7	1
6	•	•	•	•	•
•	•	•	•	•	•

b. Conventional Core Storage Configuration

Figure 9 Core Storage Image

In Figure 10a and 10b is an example of the same number of paired classes, but the data pairs are more widely scattered. In this example, the conventional data storage required is  $14 \times 12$  or 168 core locations. The present scheme still required only 21 core locations.

### C. Output Display

To display the arrays as a joint probability distribution, the first location in the  $NP_y$  array is examined and a decremental counter is set equal to this value. All the data points in the  $NP_x$  array that are paired with this  $NP_y$  value, are collected along with their number of occurrences  $NKNT(i)$ , and stored in a working array. This working array is sorted in ascending order for printing from left to right across the print paper. A print line is loaded with blank characters and the blank character is replaced with the number of occurrences in that location, if any exist. The number of occurrences is designated by an alphanumeric character of some hierarchy ordered by the user. The print line is then output to the printer. The next location in the  $NP_y$  array is examined and the counter is decreased by one. If the  $NP_y$  value is less than the counter, a print line filled with blank characters is printed and tagged with the value of the counter. The counter is then decremented and compared with the  $NP_y$  value again. If there is a comparison, then the above procedure is repeated. This continues until the  $NP_y$  array is exhausted.


### D. Data Problem Parameters

NCH	Total number of channels on input tape
NSPS	Samples per logical record or scan line
NSCANS	Number of logical records or scan lines to process
NSKIP	Initial physical records to skip before processing
NSTART	Starting sample number



$NP_x(6)_1$	$NP_y(12)_1$	$NKNT(6)_1$
• $(12)_2$	• $(8)_2$	• $(8)_2$
• $(8)_3$	• $(7)_3$	• $(12)_3$
• $(2)_4$	• $(7)_4$	• $(8)_4$
$(8)_5$	$(6)_5$	$(1)_5$
$(14)_6$	$(5)_6$	$(7)_6$
$(2)_7$	$(3)_7$	$(6)_7$

a. Core Storage Configuration



b. Conventional Core Storage Configuration

Figure 10 Core Storage Image

NSTOP	Stopping sample number
LTN	Logical tape unit to load input data
NOJP	Number of paired joint probabilities to process
IMX	X channel select
IMY	Y channel select
SCALE	Used to scale data
BIAS	Used to shift data

## 7. BOUNDARY MAPPING

A concerted effort has been made to improve boundary mapping techniques and to extend these ideas and techniques in order to classify different homogeneous areas of ground scene data. This section briefly describes one of several boundary enhancement techniques, which were investigated, and contains examples of test cases and problem parameter inputs.

The technique employed in this computer program, incorporates a moving rectangle made up of four adjacent resolution elements moved successively through the data. The configuration, produced by the magnitude of any four adjacent resolution elements connected by an imaginary path, will be defined as the area. Iso-metric displays of the ground scene (Figure 11) show different area configurations produced by any four adjacent resolution elements. The possible area configuration models are shown in Figure 12. From these configurations, the equations for calculating the area were derived, based on two cases presented by the data. Case I is the area produced by four adjacent resolution elements along the Y and Z plane, and case II is the area produced by four adjacent resolution elements along the X and Z plane. The equations that were derived ( $A_1$ ,  $B_1$ ,  $C_1$  for case I and  $A_2$ ,  $B_2$ ,  $C_2$  for case II) are shown in Figure 13a.

Several equations that appear here are redundant and are eliminated by combining similar equations. The composite test statements that determine which equation to use, are shown in Figure 13b, and a flow diagram of the decision logic incorporated in the computer program, is shown as Figure 14.




Figure 11 Isometric Display of Ground Scene




Figure 12 Area Configurations Produced by Four Adjacent Data Samples

CASE I

$$\begin{aligned}
 & \frac{1}{4}[(X_n, Y_n) - (X_n, Y_{n+1}) - (X_{n+1}, Y_n) + (X_{n+1}, Y_{n+1})] \\
 & \frac{1}{2}[(X_n, Y_n) - (X_n, Y_{n+1}) + (X_{n+1}, Y_n) - (X_{n+1}, Y_{n+1})] \\
 & \frac{1}{2}[(X_n, Y_n) + (X_n, Y_{n+1}) - (X_{n+1}, Y_n) - (X_{n+1}, Y_{n+1})] \\
 & \frac{1}{4}[-(X_n, Y_n) + (X_n, Y_{n+1}) + (X_{n+1}, Y_n) - (X_{n+1}, Y_{n+1})] \\
 & \frac{1}{2}[(X_n, Y_n) + (X_n, Y_{n+1}) - (X_{n+1}, Y_n) - (X_{n+1}, Y_{n+1})] \\
 & \frac{1}{2}[(X_n, Y_n) + (X_n, Y_{n+1}) - (X_{n+1}, Y_n) - (X_{n+1}, Y_{n+1})]
 \end{aligned}$$

CASE II

$$\begin{aligned}
 & \frac{1}{4}[(X_n, Y_n) - (X_n, Y_{n+1}) - (X_{n+1}, Y_n) + (X_{n+1}, Y_{n+1})] \\
 & \frac{1}{4}[(X_n, Y_n) - (X_n, Y_{n+1}) + (X_{n+1}, Y_n) - (X_{n+1}, Y_{n+1})] \\
 & \frac{1}{2}[-(X_n, Y_n) + (X_n, Y_{n+1}) - (X_{n+1}, Y_n) + (X_{n+1}, Y_{n+1})] \\
 & \frac{1}{4}[-(X_n, Y_n) + (X_n, Y_{n+1}) + (X_{n+1}, Y_n) - (X_{n+1}, Y_{n+1})] \\
 & \frac{1}{4}[(X_n, Y_n) - (X_n, Y_{n+1}) - (X_{n+1}, Y_n) + (X_{n+1}, Y_{n+1})] \\
 & \frac{1}{2}[(X_n, Y_n) - (X_n, Y_{n+1}) + (X_{n+1}, Y_n) - (X_{n+1}, Y_{n+1})]
 \end{aligned}$$

(a)

COMPOSITE TEST STATEMENTS

$$\left. \begin{aligned}
 & X_n, Y_n > X_n, Y_{n+1} \\
 & X_{n+1}, Y_n < X_{n+1}, Y_{n+1} \\
 & X_{n+1}, Y_{n+1} > X_n, Y_{n+1}
 \end{aligned} \right\} A(1)$$

$$A(2) \left\{ \begin{aligned}
 & X_n, Y_n < X_n, Y_{n+1} \\
 & X_{n+1}, Y_n > X_{n+1}, Y_{n+1} \\
 & X_n, Y_n < X_{n+1}, Y_n
 \end{aligned} \right.$$

$$\left. \begin{aligned}
 & X_n, Y_n < X_n, Y_{n+1} \\
 & X_{n+1}, Y_n > X_{n+1}, Y_{n+1} \\
 & X_n, Y_n > X_{n+1}, Y_n
 \end{aligned} \right\} B(1)$$


$$B(2) \left\{ \begin{aligned}
 & X_n, Y_n > X_n, Y_{n+1} \\
 & X_{n+1}, Y_n < X_{n+1}, Y_{n+1} \\
 & X_{n+1}, Y_{n+1} < X_n, Y_{n+1}
 \end{aligned} \right.$$

$$\left. \begin{aligned}
 & X_n, Y_n < X_n, Y_{n+1} \\
 & X_{n+1}, Y_n < X_{n+1}, Y_{n+1}
 \end{aligned} \right\} C(1)$$

$$C(2) \left\{ \begin{aligned}
 & X_n, Y_n > X_n, Y_{n+1} \\
 & X_{n+1}, Y_n > X_{n+1}, Y_{n+1}
 \end{aligned} \right.$$

(b)

Figure 13 Area Equations for Four Adjacent Data Samples



\* H = Area in Horizontal      V = Area in Vertical Direction

Figure 14 Flow Diagram of Decision Logic

A probability density distribution of the area is calculated for each channel of data and every scan. An estimate of this probability density function is obtained digitally by dividing the range for X into an appropriate number of class intervals, say  $d_i$ , and by tabulating the number of occurrences in each of these intervals. The number of occurrences  $N_i$  in each interval satisfies the equation

$$N = \sum_{i=0}^{k-1} N_i$$

where  $k$  = number of class intervals and  $N$  is the total population.

This number sequence  $\{N_i\}$  is found by

$$N_1 = \text{Total number of } X: X \leq d_1$$

$$N_2 = \text{Total number of } X: d_1 < X \leq d_2$$

$$N_3 = \text{Total number of } X: d_2 < X \leq d_3$$

.

.

.

$$N_k = \text{Total number of } X: d_{k-1} < X \leq d_k$$

A plot of the probability distribution of channel 3 and channel 12, both horizontal and vertical, are shown in Figures 15 and 16. These plots reflect the distribution of one scan of data, in particular, scan number 5. The criterion to determine if a resolution element reflects a change in a homogeneous population of ground scene is the mean of the probability distribution of the area plus its associated  $\sigma$ . All area calculations of four adjacent resolution elements that fall outside of the mean plus  $\sigma$  will be flagged as a boundary.




Figure 15 Boundary Determination, Probability Distribution Channel 3






Figure 16 Boundary Determination, Probability Distribution Channel 12

The mean area of the probability distribution,  $P(A)$ , is calculated by

$$\overline{P(A)} = \frac{\sum_i P(A_i) A_i}{\sum_i P(A_i)} \quad i=1,2,\dots,MAX$$

on  $\sigma$  by

$$\sigma = \left\{ \frac{\sum_i P(A_i) A_i^2}{\sum_i P(A_i)} - \left( \overline{P(A)} \right)^2 \right\}^{1/2} \quad i=1,2,\dots,MAX$$


In the test cases, all 12 channels were used, except for two cases where channel 3 and channel 12 were run separately, and boundary flags set for each channel. The final decision for determining the boundary, is based on an input parameter selected by the user. The number of channels indicating a boundary has to be greater than this value. In Figure 17 only channel 12 was used. This produced too many boundaries and the separation of different homogeneous areas was not clearly defined. In Figure 18 only channel 3 was used; this produced too few boundaries. Figure 19 shows all 12 channels with at least seven reflecting boundaries (Input Option); this produced too few boundaries. Figure 20 shows at least three channels of the 12 reflecting boundaries which produced too many boundaries. Figure 21 produces the best boundary map which uses at least four channels of the 12 total.

SCAN 1-120

RESOLUTION ELEMENT 1-222

34

SCAN



RESOLUTION ELEMENT

Figure 17 Boundary Determination Channel 12 (Purdue C1)

SCAN 1-120

RESOLUTION ELEMENT 1-222




Figure 18 Boundary Determination Channel 3 (Purdue C1)

SCAN 1-120

RESOLUTION ELEMENT 1-222




Figure 19 Boundary Determination Channels 7 of 12 (Purdue C1)

SCAN 1-120

RESOLUTION ELEMENT 1-222




Figure 20 Boundary Determination Channels 3 of 12 (Purdue C1)

SCAN 1-120

RESOLUTION ELEMENT 1-222



Figure 21 Boundary Determination Channels 4 of 12 (Purdue C1)

### A. Data Problem Parameters

NSCANS	Number of scans or logical records to process an input tape
NSTART	Starting resolution element in the scan
NSPS	The number of resolution elements or columns to process from each scan ( $\leq 255$ )
NCH	Number of channels present on input tape
NVAR	Number of variables or intervals desired in calculating the probability distribution; Maximum of 2000.
NSYM	Number of alphanumeric characters to display boundaries (note: At the present only two characters are used, blanks and dots, no boundary or yes boundary respectively).
ISUM	Total number of channels used in initial boundary calculation
NTEST	Number of channels (plus one), of ISUM, necessary for a final boundary decision
NBTLG	Number of bits per word on the input tape
MODE	Mode of input tape (2=non-FORTRAN, 1=FORTRAN)
NSKIP	Number of records to skip before processing input data
NCRE	Data increment
NBLK	Number of raster counts per character desired in displaying boundary on the Stromberg-Carlson 4020 plotter recorder
INCX	Raster counts incrementation in the X direction
INCY	Same as above in the Y direction
NSTX	Starting position or frame along the X axis
NSTY	Starting position on frame along the Y axis
NWHICH	Channel number desired in calculation of boundary



## 8. CHANNEL ALIGNMENT

In recent months there has been an increasing demand to process and analyze data collected by array cameras using different filters in the frequency spectrum. In order to analyze data from this camera source, the camera film is digitized and the digitizing process is carried out separately for each filtered film. Gross errors are introduced into the data, mainly missalignment of the film when being digitized by a densitometer. This missalignment must be compensated for before the digitized data can be merged and processed. A process was developed to align the digitized data sets by a matching matrix technique.

Boundaries separating homogeneous areas are calculated from each data set (see section 7) and the boundaries of each data set are correlated and matched. One particular technique proposed was the use of NXM data matrix for each data set where one set is assigned the reference channel and the other sets are correlated with the reference channel by moving the matching matrix successively through the selected data area.

The correlation of the reference channel with other channels is done by matching or correlating a resolution element from the reference channel with all resolution elements in the matching matrix of other channels. If there exists a match or correlation of boundaries, then a cell in the matching matrix display at those coordinates is incremented. The NXM matching matrix is moved by one resolution element, and the next resolution element from the reference channel is matched or correlated with all the resolution elements in the matching matrix of other channels. If there exists a match or correlation of boundaries, then a cell in the matching matrix display at those coordinates is again incremented. This continues as the matching matrix is moved successively through the selected data interval.

An expanding and collapsing technique is employed at the beginning and end of the data set to eliminate edge effects and loss of data. As the NXM matching matrix is moved successively through the data set, the correlation of the two channels, if a correlation exists, is accumulated at the beginning of the data set at the matching matrix display coordinates MATRIX (i,j) going across, where

$$i = \frac{N}{2} - b+1, \frac{N}{2} - b+2, \dots, N; k = 1, 2, 3, \dots, \frac{N}{2},$$

and going down where

$$j = \frac{M}{2} - b+1, \frac{M}{2} - b+2, \dots, M; k = 1, 2, 3, \dots, \frac{M}{2}.$$

This continues until the entire matching matrix is within the objective data, thus eliminating the edge effect. Once the matching matrix is within the objective data then  $i = 1, 2, 3, \dots, N$ ; and  $j = 1, 2, 3, \dots, M$ . Upon termination of the matching matrix at the end of a data set, a collapsing technique is employed. This technique is the same as the expanding technique except the accumulation at the end of the data set at the matching matrix display coordinates MATRIX (j,i) is  $i = 1, 2, 3, \dots, N-k$ , where  $k = 1, 2, 3, \dots, \frac{N}{2}$ ; and  $j = 1, 2, 3, \dots, M-k$ , where  $k = 1, 2, 3, \dots, \frac{M}{2}$ .

The matching matrix is then printed for each combination of correlations. No boundary and boundary correlation of two data channels (0,1), and boundary and boundary correlation of two data channels (1,1). Alignment shifts can be performed by locating the peaks in the NXM matrix where boundaries of two channels are matched. The matching matrix is shown in the output example. This peak occurred at coordinates (-5, +4), therefore, the channel being correlated with the reference should be shifted -5 data records and +4 resolution elements to align the two channels.

This technique corrects for any horizontal and vertical alignment satisfactorily, however it does not correct for any skewness introduced, while the film is being digitized, or any distortion in the camera array angles. A technique that fully corrects for this type of missalignment is presently being developed, but due to inadequate computer turnaround time, results are not available.


#### A. Computer Program

A program was written to match and correlate up to three data channels and as many different intervals of a data set as desired. This will enable the user to calculate the alignment in areas of the data set where boundaries are clear and can be detected. Input to the program is three FORTRAN formatted fixed point binary tapes containing boundary flags (fixed point integer 1 for boundary and 0 for areas that are homogeneous).


#### B. Data Problem Parameters

NTIMES	Number of sections to correlate
LT9	Logical unit to load input tape number one
LT10	Logical unit to load input tape number two
LT11	Logical unit to load input tape number three
NSTART	Starting resolution element
NSTOP	Final resolution element
NSCANS	Number of scans in the matching matrix
NSPS	Number of resolution elements across the scan in the matching matrix
NREFX	Starting resolution element in the reference channel; Tape number one.
NREFY	Starting scan number in the reference channel; Tape number one.
NCH1X	Starting resolution element in the channel to be correlated; Tape number two.
NCH1Y	Starting scan in the channel to be correlated; Tape number two.
NCH2X	Starting resolution element in the channel to be correlated; Tape number three.
NCH2Y	Starting scan in the channel to be correlated; Tape number three.

### C. Program Flow Chart



Channel Alignment



Channel Alignment (Concluded)

# OUTPUT EXAMPLE

MATCHING MATRIX (1 AND 1)

CH 2 WITH CH 1

••	174	176	176	182	192	160	170	193	198	192	167	182	198	196	159	176	168	161	169	181	156	171	171	165	147	146	167	••
••	171	178	172	183	185	164	169	185	193	210	189	173	181	196	187	178	175	171	190	176	179	165	178	187	157	158	173	••
••	177	179	178	185	204	174	170	184	208	212	197	183	184	184	183	168	177	177	178	184	189	168	171	173	168	168	179	••
••	189	191	183	193	204	197	185	193	205	201	195	199	186	182	193	184	180	178	178	192	196	169	163	187	176	162	176	••
••	182	179	208	192	202	218	208	194	202	227	212	197	214	209	192	193	198	186	181	201	193	173	182	195	171	179	185	••
••	172	204	213	193	191	196	196	202	199	218	212	202	215	216	198	218	227	188	189	192	199	196	201	191	174	184	190	••
••	186	185	201	189	198	194	212	196	198	230	221	225	231	216	216	209	217	200	204	195	187	193	197	200	175	185	167	••
••	193	167	199	187	175	183	191	215	216	236	232	214	226	245	213	206	216	197	197	185	177	190	185	193	188	181	178	••
••	163	184	200	171	189	190	195	207	219	237	220	221	232	214	221	226	212	211	211	197	198	205	205	193	180	196	182	••
••	208	187	193	183	194	204	202	211	249	238	240	226	233	232	223	236	216	197	212	207	208	222	209	211	210	197	191	••
••	210	194	188	186	192	218	204	218	256	239	249	250	225	204	217	234	213	192	192	212	220	200	203	209	200	209	198	••
••	207	206	189	197	195	218	200	207	243	236	246	243	234	233	249	234	200	193	199	219	220	203	204	208	192	211	195	••
••	198	222	230	186	194	204	197	212	241	235	232	223	237	236	236	227	216	186	195	203	217	216	210	218	190	210	200	••
••	193	196	221	187	205	206	195	225	255	224	236	240	220	226	207	208	212	218	224	211	222	210	219	224	207	198	195	••
••	194	183	211	189	194	189	201	219	239	242	244	225	230	243	206	216	209	214	212	216	227	232	233	214	208	213	175	••
••	184	164	196	192	192	187	208	210	215	238	239	222	232	222	220	211	220	202	190	201	218	230	224	200	202	209	190	••
••	183	190	192	186	194	212	196	199	195	225	218	223	197	222	224	226	218	194	210	201	203	228	221	216	209	205	174	••
••	176	164	190	188	202	189	168	175	196	222	218	204	201	211	223	217	212	221	231	220	225	228	222	219	224	212	199	••
••	177	176	192	173	172	180	165	171	195	212	211	203	191	203	224	227	209	201	201	239	233	230	217	221	219	215	213	••
••	183	184	203	187	185	181	169	202	207	211	213	200	195	208	224	234	227	195	196	226	210	167	202	204	206	205	206	••
••	181	182	189	194	178	168	181	205	210	224	230	199	190	208	218	213	214	204	217	218	208	204	192	189	219	207	194	••
••	159	162	182	187	187	175	175	201	209	219	214	202	193	209	212	202	200	221	210	192	188	214	225	184	204	211	196	••
••	170	161	165	173	191	186	191	187	203	210	207	200	218	208	205	224	211	209	217	190	200	204	207	204	197	198	191	••
••	181	160	161	174	182	195	195	191	213	215	225	212	217	190	223	226	222	207	215	209	202	194	208	211	184	172	166	••
••	152	152	152	191	165	190	180	181	183	226	224	205	214	183	208	222	232	209	200	209	215	196	211	212	210	189	191	••
••	144	149	155	173	170	178	207	188	196	217	225	186	198	188	191	200	221	204	204	197	223	209	181	193	199	195	199	••
••	144	151	158	175	162	154	178	192	200	205	204	200	206	194	190	214	216	216	199	195	207	212	188	184	210	191	209	••

## 9. CHANNEL REGISTRATION

Registration of digital images of the digitized film processed from a multiple camera array system, has become necessary due to the rotational, translation and scaling errors introduced during processing. A coarse alignment is made by employing the matching matrix technique but this only corrects for a horizontal or vertical shift in the digital images for alignment. There exist errors in the digital images, such as rotation and translation errors, which have to be corrected by a more effective means. A technique which will accomplish this is presently being developed and has been demonstrated. Computer results are not available, due to contract expiration which prevented finalizing the analysis, therefore, no illustrations are shown.

The technique requires generating boundary maps of the digital images and a manual technique is used to correlate similar areas of the digital images with each other. A good sampling of the entire scene is made which provides enough input to a set of equations (equations are presently being derived and improved upon) to calculate coefficients for each digital image combination. When used with the x and y coordinates of a reference channel, position pointers are calculated giving the respective x and y coordinates of the channels to be aligned. Data points are taken from these coordinates and placed at the coordinates of the reference channel. All channels are then output to magnetic tape becoming merged for further processing.

A program was written to overlay any combination of digital images containing boundary information (0 and 1) that have been registered and merged. This overlay program produces a map showing the location of boundaries and homogeneous areas that are similar. This program is used in conjunction with the registration process and evaluating the accuracy of the registration process.

After the digital images are aligned satisfactorily the registration process can be carried out on the raw data and processed as desired, or the merged boundary tapes can be processed.

### A. Computer Program


A computer program was written to register multiple digital images using boundary information or raw data. The program inputs a reference channel and the x and y coordinates of data points from the reference channel are input to a subroutine FETCH which returns through the call statement the x and y coordinates of the channel to be aligned. Subroutine FETCH contains DATA statements with coefficients used in the calculations. These DATA statements can be changed to reflect coefficients of different digital images.

### B. Data Problem Parameters


NSPS	Number of samples per scan
NCHAN	Number of channels on input tape
NSCANS	Number of scans to process
NSKIP1	Initial position of tape number one
NSKIP2	Same as above for tape number two
NSKIP3	Same as above for tape number three




### C. Program Flow Chart



Channel Registration



Channel Registration



Channel Registration (Concluded)

## 10. SPECTRAL DISCRIMINATION

Capabilities have been developed to discriminate ground scene features using computer techniques with digitized images. These capabilities are available at MSFC for analysis and interpretation of earth resources flight data. Computer programs and algorithms were developed during this contract period, March 22, 1971 to September 22, 1972, under the auspices of the National Aeronautics and Space Administration, with Mr. Robert Jayroe COR. The mathematical rationale used in the development of these computer programs are to be published by Mr. Robert Jayroe in a NASA report entitled "Unsupervised Spatial Clustering with Spectral Discrimination."

INTENTIONALLY BLANK

## ERFDP USERS MANUAL


### SECTION II INTRODUCTION

Processing earth resources data in the future will require a somewhat automatic approach due to the volume of data and the extent of analysis required to interpret the data. This requires a complex data processor designed to maintain an automatic data processing (ADP) environment for the user. The processor is designed using independent modules with an executive program driving each module. A block diagram depicting this modular structure is shown as Figure 22.

This processor uses an overlay technique, which compiles and communicates with all modules, but only executes modules selected by the user. The concept of using overlays provides capabilities for processing input data, through all the program modules sequentially or only selected modules as desired. Each module can be improved upon, expanded and modified independently of other modules, and each module can be improved or modified in a 32K core storage environment irrelevant to the other modules (see Figure 23).


This concept has the disadvantage of having to utilize an intermediate storage tape, which necessitates executing read/write commands, which are certainly time-consuming. However, the advantages outweigh the disadvantages significantly by providing versatility in the overall function. To further improve on the efficiency of the program, the read/write commands use alternate input/output channels when possible to eliminate, in most cases, the computer being in a "wait" condition due to either channel "A" or channel "B" being busy.

The overlay concept entails having a main program which calls each individual module as requested by the user. This keeps the overall processing contained in one large program and each program module is brought into the computer, compiled, overlay structures created, and then output onto an overlay tape. All modules are treated in this fashion regardless of which and how many are to



Earth Resources Flight Data Processing

Figure 22 Block Diagram Depicting Modular Structure



Tape Assignments:

LT1 = A3

LT9 = B5

LT10 = A6

LT11 = B6

LT12 = A7

LT13 = B7

OPT = (Optional)

Earth Resources Flight Data Processor


Figure 23 Block Diagram ERFDP



be used. Each module to be executed is brought into the computer in a "transit" area (see Figure 24), and upon completion, another module, if requested, is brought into the same "transit" area to be executed. A common area in the computer is used to store information that may be used by more than one module. Each module has access to this common area at any time it occupies the "transit" area.

# 1. EARTH RESOURCES FLIGHT DATA PROCESSOR

The ERFDP is comprised of seven separate and independent modules which reside in computer memory only while being executed. Module seven consists of three lower level modules that are called into memory to perform their function automatically when module seven is requested by the user. The segmented structure appears as diagrammed.



Each module can be called into core memory and executed independently and in any order with the exception of module seven. Module six has to be executed prior to module seven, since the boundary mapping output is input to module seven. If module six has been run previously and a boundary mapping output tape is available, then module seven can be executed alone.




Figure 24 Block Diagram ERFDP

A dimensional variable called MODULE is dimensioned 8, which sets aside eight memory locations to store a users request for module execution. The number of locations filled depends upon the number of modules requested to be executed by the user. The remaining locations contain zeroes and when the processor encounters a zero while examining the list, it terminates under system control.

#### A. Data Problem Parameters Example Setup

```
$DATA
$INIT
MODULE = 1,2,4,6,7      User request modules 1,2,4,6,7
                        to be executed and in that order.
$END
```

#### B. Input Tapes

Unit - Users option under individual modules (A6 recommended)  
Type - Reference individual modules

#### C. Output Tapes

Reference individual modules

## 2. MODULE ONE

Module one when called into memory calculates a probability density function for any number of channels not to exceed 12. The module provides options to calculate probability density functions on selected channels also.

### A. Data Problem Parameters Example Setup

```
$INPUT1
NCH = 3           Number of input channels
NSPS = 794        Number of samples per record
NSCANS = 500      Number of scans or records to process
NSTART = 1        Starting sample number
NSTOP = 794       Stopping sample number
NBTLC = 12        Bit length of input data word
MODE = 2          Signifying non-FORTRAN input tape
ITYPE = 0         Fixed point input; ITYPE = 1 ; Floating
                  point 36-bit word input
MSFC = 0          Not MSFC scanner format; MSFC = 1; MSFC
                  scanner format
LTN = 10          Logical tape unit of input tape
NSKIP = 2         Skip first two data records
NCRE = 1          Data increment to process
XMAX = 1200.0     Maximum value in data set
XMIN = 300.0      Minimum value in data set
NOCHS = 3         Number of channels to calculate probability
                  density function
NWHICH = 1,2,3    Calculate probability density function on
                  channels 1,2, and 3
$END
7/8
```

### B. Input Tapes


Unit - Users option under input parameters


Type - Any odd parity binary, 3-bit modulus, fixed point with word lengths  $\leq$  36 bits, or floating point.

### C. Output Tapes

None (only print output)

#### D. Program Flow Chart





Multiple Channel Probability  
Distribution (concluded)

OUTPUT EXAMPLE  
PROBABILITY DISTRIBUTION

<u>AMPLITUDE</u>	<u>CH 1</u>	<u>CH 2</u>	<u>CH 3</u>	<u>CH 4</u>	<u>CH 5</u>	<u>CH 6</u>	<u>CH 7</u>	<u>CH 8</u>	<u>CH 9</u>	<u>CH 10</u>	<u>CH 11</u>	<u>CH 12</u>
-1.5	0	0	0	0	0	0	0	0	0	0	0	0
-1.4	0	0	2	0	2	0	0	0	0	0	1	0
-1.3	0	0	3	0	0	0	0	0	0	0	0	0
-1.2	1	0	9	0	5	0	0	1	0	0	1	0
-1.1	0	0	21	0	7	0	0	0	1	1	8	0
-1.0	5	0	29	0	15	1	0	1	0	0	22	0
- .9	4	0	35	0	17	1	0	3	2	4	31	0
- .8	8	1	39	0	34	2	3	9	7	8	47	0
- .7	12	0	48	0	39	8	8	18	20	16	60	0
- .6	24	7	55	1	47	12	12	22	25	30	55	0
- .5	21	11	66	0	51	22	22	38	40	40	40	0
- .4	38	5	58	2	55	31	41	47	48	52	27	0
- .3	45	12	49	12	49	49	70	50	55	60	11	0
- .2	57	22	42	18	44	66	82	54	62	72	6	5
- .1	59	37	33	20	39	72	96	47	51	55	5	1
0	62	44	25	35	33	62	79	41	45	52	0	8
.1	58	48	19	30	25	40	62	35	39	31	1	16
.2	51	49	12	41	18	22	38	25	25	20	0	27
.3	47	56	6	54	7	12	12	17	16	15	0	32
.4	35	52	1	61	8	8	10	12	8	7	0	39
.5	25	40	0	55	2	2	7	8	5	3	0	47
.6	22	32	1	45	1	0	2	0	1	5	0	52
.7	8	24	0	40	0	1	1	2	0	1	0	65
.8	4	16	0	35	1	0	0	0	0	0	0	72
.9	2	8	0	28	0	0	0	0	0	0	0	58
1.0	3	7	0	20	0	0	0	0	0	0	0	46
1.1	1	1	0	12	0	0	0	0	0	0	0	39
1.2	0	0	0	7	0	0	0	0	0	0	0	22
1.3	1	1	0	0	0	0	0	0	0	0	0	7
1.4	0	0	0	1	0	0	0	0	0	0	0	1
1.5	0	0	0	0	0	0	0	0	0	0	0	0

NUMBER OF OCCURRENCES

### 3. MODULE TWO

Module two outputs on print paper and/or Stromberg-Carlson 4020 recorder, the quantized levels of a data set with alpha-numeric characters displaying specific quantized levels. Alpha-numeric characters can be selected and input to the module on a card included in the input problem parameters to provide different shading for certain levels. This module displays only one channel per computer pass, and that one channel is optional and selected by the user.

#### A. Data Problem Parameters Example Setup

\$INPUT2	
NCH = 3	Number of channels on input tape
NSPS = 794	Number of samples per record or scan
NSCANS = 500	Number of scans to process
NSKIP = 2	Number of scans to skip before processing
NSTART = 1	Starting sample number
NSTOP = 120	Stopping sample number
ITERM = 6	Number of passes processing 120 samples each pass
N = 11	Number of levels plus 1
ICHAN = 3	Channel used in mapping
IPRT = 1	Option to print
IPLT = 1	Option to plot
INCX = 0	Increment in x direction for each sample (rasters)
INCY = 8	Increment in y direction for each sample (rasters)
NSTX = 0	Starting x coordinates on plot frame
NSTY = 0	Starting y coordinates on plot frame
NBTLG = 12	Bit length of input data words
MODE = 2	Signifies non-FORTRAN
ITYPE = 0	Fixed point input data; ITYPE = 1 ; Input data floating point 36-bit words
MSFC = 0	Not MSFC scanner format; MSFC = 1; MSFC scanner format



NCRE = 1                      Data increment  
LTN = 10                     Logical tape unit of input tape  
IOPT = 0                    Signifies automatic quantization

\$END

\$GRYLYL

GLVL = 1., 2., 3., 4., 5., 6., 7., 8., 9., 10., 11.

1., 2., 3., 4., 5., 6., 7., 8., 9., 10., 11.

°

°

°

1., 2., 3., 4., 5., 6., 7., 8., 9., 10., 11.

\$END

7/8

#### B. Input Tapes


Unit - Users option under input parameters


Type - Any odd parity binary, 3-bit modulus, fixed point,  
with word length  $\leq$  36 bits or floating point.

#### C. Output Tapes


None (only print output)

# D. Program Flow Chart





Grey Level Mapping




Grey Level Mapping  
(concluded)

OUTPUT EXAMPLE  
PURDUE FLIGHT LINE C1  
AUTOMATIC QUANTIZED GREY LEVEL

RESOLUTION ELEMENT 1-111 SCANS 1-120

SCAN




RESOLUTION ELEMENT

OUTPUT EXAMPLE  
PURDUE FLIGHT LINE C1  
AUTOMATIC QUANTIZED GREY LEVEL

RESOLUTION ELEMENT 112-222 SCANS 1-120

SCAN



RESOLUTION ELEMENT

#### 4. MODULE THREE

Module three calculates contour lines throughout an input data set depicting elevation, altitude, temperature or boundary contours. The contour lines are output and displayed by the Stromberg-Carlson 4020 plotter. Frame butting in the module provides for continuous contour plotting for infinite data sets. The contour lines can be scaled by utilizing the block size option (BLK) in the input problem parameters.

##### A. Data Problem Parameters

\$INPUT3	
NCH = 1	Number of channels
NSPS = 90	Number of samples in a scan (record)
IRW = 11	Logical tape unit for input data
NCHAN = 1	Channel number
NSNCRE = 1	Number of scans to increment
NPCRE = 1	Number of samples to increment
NPTSL = 1	Lower starting point
NPTSU = 90	Upper stopping point
NBTLG = 36	Bit length of input data word
MODE = 1	FORTTRAN formatted (1) or non-FORTTRAN (2)
ITYPE = 0	Fixed point input ITYPE = 1, floating point input
MSFC = 0	MSFC = 1; MSFC scanner format
NSKIP = 0	Number of records to skip
MAXSCN = 100	Total number of scans to process
MSZX = 90	Data block size in x (samples)
MSZY = 8	Data block size in y (scans)
BLK = 8.0	Plot frame block size in rasters
FHINC = 10.0	Labeling increment
ZMIN = 8.0	Minimum label
ZMAX = 138.0	Maximum label
LAB = 1	Label every interval
\$END	
7/8	

### B. Input Tapes

Units - Optional under input data


Type - Any odd parity binary, 3-bit modulus, fixed point,  
with word lengths  $\leq 36$  bits, or floating point.

### C. Output Tapes


SC 4020 Stromberg-Carlson formatted tape




#### D. Program Flow Chart




Contour Level Plotting



Contour Level Plotting



Contour Level Plotting



Contour Level Plotting  
(concluded)

OUTPUT EXAMPLE

SCAN 1-120

RESOLUTION ELEMENT 1-222



RESOLUTION ELEMENTS  
BOUNDARY CONTOURS (PURDUE C1)

## 5. MODULE FOUR

Module four displays a two-dimensional plot of three-dimensional data where only one single array of data is input and the data samples are ordered in an XY coordinate system, where Y is the scan line count and X is the resolution element in the scan. Data sets of infinite length can be displayed on the SC4020 recorder. The module provides for multiple passes through the data set in order to view the entire data set in sections.

### A. Data Problem Parameters Example Input

\$INPUT4

NCH = 12	Number of channels on input data tape
NSPS = 222	Number of resolution elements per scan
NSKIP = 0	Initial records to skip
NBTLG = 12	Bit length of the input data word
MODE = 1	FORTTRAN formatted (1) or non-FORTTRAN formatted
IRW = 10	Logical tape unit to load input
NCHAN = 6	Channel selected to be plotted
NSNCRE = 1	Scan incrementation
NPCRE = 1	Resolution element incrementation
ITYPE = 1	Fixed point input (0) or Floating point input (1)
MSFC = 0	MSFC scanner format (1) or not MSFC scanner format
NPTSL = 1	Lower resolution element to start
NPTSU = 111	Upper resolution element to stop
MAXSCN = 120	Scan lines to be processed
XMIN = 0.0	Minimum value for scaling the X axis
XMAX = 222.0	Maximum value for scaling the X axis
YMIN = 0.0	Minimum value for scaling the Y axis
YMAX = 255.0	Maximum value for scaling the Y axis
NBLSZX	The distance separating the plotted points in the X direction

NBLSZY	The distance separating the plotted points in the Y direction
NSECT = 2	Two passes through the data to plot the data set in two sections
NSMOV = 0	No smoothing on input data
NDIREC = 1	Orientation of the isometric left view (-1) or right view (1)
\$END	
7/8	

#### B. Input Tapes


Unit - Users option under input parameters

Type - Any odd parity binary, 3-bit modulus, fixed point with word lengths  $\leq 36$  bits, or floating point binary.

#### C. Output Tapes


Unit - A8 SC4020

#### D. Program Flow Chart




Isometric Program Display






Isometric Program Display




Isometric Program Display




Isometric Program Display  
(concluded)

OUTPUT EXAMPLE  
FLIGHT LINE C1  
SCANS 1-43 &  
RESOLUTION ELEMENTS 1-111  
ROTATED CLOCKWISE  
CHANNEL 8 0.58-0.62 (MICRONS)



OUTPUT EXAMPLE  
FLIGHT LINE C1  
SCANS 1-43  
RESOLUTION ELEMENT 1-111  
ROTATED COUNTER-CLOCKWISE  
CHANNEL 8 0.58-0.62 (MICRONS)



## 6. MODULE FIVE

Module five calculates a joint probability density function from two time-series data traces selected by the user in the data problem parameters. The program provides for multiple passes through the data set for multiple joint probability density functions. The raised data points are classified and stored in one single array along with its associated occurrences of like data pairs. The joint pairs are sorted vertically in descending order and horizontally for each print line in ascending order.

### A. Data Problem Parameters Example Setup

```
$INPUT5
NCH = 12          Total number of channels on input tape
NSPS = 222       Samples per logical record or scan line
NSCANS = 920     Number of logical records or scan lines
                  to process
NSKIP = 0        Initial physical records to skip before
                  processing
NSTART = 2       Starting sample number
NSTOP = 222     Stopping sample number
LTN = 10        Logical FORTRAN IV tape unit
NOJP = 2        Number of paired joint probabilities to
                  process
IMX = 4,3       Use channel 4 and 3 in X
IMY = 6,7       Use channel 6 and 7 in Y
SCALE = 1.0     Used to scale 1
BIAS = 0        Used to shift data
$END
```

①. ①. ),/\* ABC... (Alphanumeric characters)

7/8

### B. Input Tapes


Unit - A6 (optional)

Type - Any odd parity binary, 3-bit modulus, fixed point with word lengths  $\leq 36$  bits, or floating point binary.

### C. Output Tapes


(none print output only)


# D. Program Flow Chart




Dynamic Joint Probability Distribution







Dynamic Joint Probability Distribution



Dynamic Joint Probability  
Distribution (concluded)

# OUTPUT EXAMPLE

JOINT PROBABILITY DISTRIBUTION  
X-AXIS IS 9 Y-AXIS IS 12  
DATA SWITCH HAS OCCURRED  
X-AXIS IS 12 Y-AXIS IS 9

SYMBOL	N/SYMBOL
.	0
.	3
.	6
.	9
/	12
+	15
=	18
(	21
)	24
*	27
\$	30
1	33
2	36
3	39
4	42
5	45
6	48
7	51
8	54
9	57
0	60
A	63
B	66
C	69
D	72
E	75
F	78
G	81
H	84
I	87
J	90
K	93
L	96
M	99
N	102
O	105
P	108
Q	111
R	114
S	117
T	120
U	123
V	126
W	129
X	132
Y	135
Z	138

PART 1 OF 1


214.0 X  
213.0  
212.0

```

211.0
210.0
209.0
208.0
207.0
206.0
205.0
204.0 X
203.0
202.0
201.0
200.0
199.0
198.0
197.0
196.0
195.0
194.0 X
193.0
192.0
191.0
190.0
189.0
188.0
187.0
186.0
185.0
184.0 X
183.0
182.0
181.0
180.0
179.0
178.0
177.0
176.0
175.0
174.0 X
173.0
172.0
171.0
170.0
169.0
168.0
167.0
166.0
165.0
164.0 X
163.0
162.0
161.0
160.0

```

159.0	.
158.0	.
157.0	.
156.0	.
155.0	.
154.0	X
153.0	.
152.0	.
151.0	.
150.0	.
149.0	.
148.0	.
147.0	.
146.0	.
145.0	.
144.0	X
143.0	.
142.0	.
141.0	.
140.0	.
139.0	.
138.0	.
137.0	.
136.0	.
135.0	.
134.0	X
133.0	.
132.0	.
131.0	.
130.0	.
129.0	.
128.0	.
127.0	.
126.0	.
125.0	.
124.0	X
123.0	.
122.0	.
121.0	.
120.0	.
119.0	.
118.0	.
117.0	.
116.0	.
115.0	.
114.0	X
113.0	.
112.0	.
111.0	.
110.0	.
109.0	.
108.0	.
107.0	.
106.0	.



## 7. MODULE SIX

Module six calculates boundaries outlining edges of homogeneous areas of ground scene data. These boundaries are displayed on print paper where a selected alphanumeric character signifies a boundary and blanks signify areas of homogeneity. This output is also displayed on the SC4020 plotter where boundaries are flagged by an alphanumeric "period." The boundary output is used in further processing to extract information for feature discrimination.

### A. Data Problem Parameters Example Setup

#### \$INPUT6

NSCANS = 120	Process 120 scans of the data set
NSTART = 1	Starting sample number
NSPS = 222	Number of samples to process; ( $\leq 255$ )
NCH = 12	Number of channels on input tape
NSYM = 49	Dimension of the Alphanumeric array
ISUM = 5	Number of channels used in calculating boundaries
NBTLG = 12	Bit length of input data word
MODE = 1	FORTTRAN formatted (1), non-FORTTRAN formatted = 2
ITYPE = 0	Input data fixed point. Floating point binary = 1
MSFC = 0	Not MSFC scanner format MSFC scanner format = 1
NSKIP = 0	Skip no records before processing
INCX = 0	Incrementation in the X direction on the plot frame between resolution elements for each scan
INCY = 4	Incrementation in the Y direction on the plot frame between resolution elements for each scan
NSTX = 0	Starting X coordinates on the plot frame
NSTY = 0	Starting Y coordinates on the plot frame
NCRE = 2	Data incrementation; Use every other data sample for boundary calculations



\$END

\$NCHUSE

NWHICH = 1,3,4,8,12

Channel selection for calculating  
boundaries

\$END

①. ③. ① \*(- =, \$+ABC ....Z12 ...90-

7/8

### B. Input Tapes


Unit - Any odd parity binary, 3-bit modulus, fixed point  
with word lengths  $\leq$  36 bits, or floating point  
binary.


### C. Output Tapes


Unit - B6

Type - Fixed point binary 1's and 0's FORTRAN formatted  
255 words or less plus 1 FORTRAN index per logical  
record.


# D. Program Flow Chart








Boundary Mapping



OUTPUT EXAMPLE

SCAN 1-120

RESOLUTION ELEMENT 1-222



Boundary Determination Channels 4 of 12 (Purdue C1)

## 8. MODULE SEVEN

Module seven consists of three submodules called into core memory sequentially to classify land use data. These modules perform spatial clustering, sequential merging, and spectral discrimination of ground scene images. The module provides an option to select multiple passes to further classify small insignificant homogeneous areas that may be overlooked or misclassified during the first pass.

The input to module seven is the boundary mapped information (see Boundary Mapping) and the raw spectral digitized images. The spatial clustering submodule searches areas on the boundary map tape that contain homogeneous areas consisting of at least 100 square resolution elements as a threshold. When this search is satisfied, this homogeneous area is identified with a number which is incremented for each separate homogeneous area. A new tape is created containing these identified clusters. The sequential merging submodule searches the tape containing the identified clusters and selects the raw spectral data associated with each cluster. Criterion parameters are calculated and the merging process takes place merging all similar clusters.

The spectral discrimination submodule, classifies the merged clusters starting with an initial class of one, with unit incrementation for each new class detected. The raw spectral data criterion parameters, for each resolution element are compared with all classification criterion parameters. If a comparison exists, then the resolution element becomes classified. If there is no comparison, the resolution element is assigned a blank or a boundary flag, (if the resolution element reflects a boundary).

If the ground scene is not classified satisfactorily, another pass can be performed reducing the homogeneous square area threshold to 36 resolution elements. This will enable smaller homogeneous areas, that were not detected by the 100-square resolution element threshold to be detected and an attempt will be made to classify these areas also.

In the output example of module seven, Figure 25 shows the initial clustering of homogeneous areas that contain at least 100 square resolution elements. Figure 26 shows the results of the sequential merging and the classifying process. In Figure 26 there exist areas that were not classified therefore an additional pass was necessary to improve the classified areas. Figure 27 shows small homogeneous areas clustered using the 36-square resolution element threshold. These areas are clusters O, P, and Q. Figure 28 shows the areas O, P, and Q, have been merged and classified which improves the classified images.

#### A. Data Problem Parameters Input Example

```

$INPUT7
NPASS = 2           Perform two passes through the clustering,
                    merging and classifying process
NCLUST = 0          Initial cluster number. Additional passes
                    can be performed on reruns, by inputting
                    the total number of classes already detected.

$END
$INPUTA
NSPS = 222          Number of resolution elements in entire
                    scan or logical record
NSCANS = 120        Number of scans to process
NCH = 12            Total number of channels on input tape
LT1 = 1             Logical tape unit for scratch tape
LT9 = 9             Logical tape unit for storage of update
                    information
LT10 = 10           Logical tape unit for raw data input
LT11 = 11           Logical tape unit for boundary map
LT12 = 12           Logical tape unit for clustered homo-
                    geneous areas
LT13 = 13           Logical tape unit containing the final
                    classified map
NSTART = 1          Starting sample number
NSTOP = 140         Stopping sample number; Process only
                    sample number 1-140 (NSTOP-NSTART + 1 ≤ 255)
NBTLG = 12          Bit length of word on input raw data tape
MODE = 1            Input data FORTRAN formatted
                    MODE = 2 non-FORTRAN formatted

```



SPATIAL CLUSTERING  
PASS 1    SCAN 1-120    RESOLUTION ELEMENT 1-140




Figure 25 Module Seven Output Example

UNSUPERVISED SPECTRAL DISCRIMINATION  
PASS 1 SCAN 1-120 RESOLUTION ELEMENT 1-140



5042

Figure 26 Results of Sequential Merging  
and Classifying Process

# SPATIAL CLUSTERING

PASS 2 SCAN 1-120 RESOLUTION ELEMENT 1-140



SCAN

Figure 27 Clustered Homogeneous Areas

Figure 28 Merged and Classified Homogeneous Areas

SCAN

107



ITYPE = 0	Input tape binary integer ITYPE = 1, floating point format
MSFC = 0	Non-MSFC scanner format; MSFC scanner has housekeeping data requiring special handling. Set MSFC = 1 if MSFC scanner data
14 = 1	Number of physical records per logical record
NCRE = 1	Data increment; NCRE = 1 use every data sample
NSKIP = 0	Initial records to skip before processing
INCX = 0	Increment in X direction on SC4020 plot frame for each sample
INCY = 8	Increment in Y direction on SC4020 plot frame for each sample
NSTX = 0	Starting X coordinate on the SC4020 plot frame
NSTY = 0	Starting Y coordinate on the SC4020 plot frame
IXXX = 10	Homogeneous area threshold samples in X
IYYY = 10	Homogeneous area threshold samples in Y direction

① ① 1234567890ABC ....(Alphanumeric characters for displaying classified homogeneous areas)

#### B. Input Tapes

Unit - A6 and B6

A6 is any odd parity binary, 3-bit modulus, fixed point with word lengths  $\leq 36$  bits, or floating point binary.

B6 is integer binary FORTRAN formatted.

#### C. Output Tapes

Units - B5 FORTRAN floating point binary  
(update information)


A7 FORTRAN fixed point binary (Cluster data)

B7 FORTRAN fixed point binary


#### D. Intermediate Tapes

Units - A3, Scratch tape only


### E. Program Flow Chart




Spectral Discrimination




Spectral Discrimination









Spectral Discrimination




Spectral Discrimination




Spectral Discrimination





Spectral Discrimination






Spectral Discrimination





Spectral Discrimination





Spectral Discrimination  
(concluded)




Figure 29 IBM 7094 Job Deck Setup

7094- INSTRUCTIONS

NAME: John Doe OP CODE: 11 STACK #     

BIN # 053 LOC: 4663 JOB: # 123456

IF EXCEEDS MAX: FAST TAPES: A B C D

☐ STR ☐ STZ ☐ DMP ☐ RETSY

INPUT TAPES

LOGIC	REEL NO	DEN	WORK LOGIC
<input checked="" type="checkbox"/> 1B SYS	<input checked="" type="checkbox"/> COMPL / ASSMBL	<u>A6</u>	<u>56565</u>
<input type="checkbox"/> SPOOK	<input checked="" type="checkbox"/> EXECUTE	<u>8</u>	<u>B6</u>
<input type="checkbox"/> OTHER	<input type="checkbox"/> PUNCH (BCD BIN)		<u>A7</u>
<input checked="" type="checkbox"/> 1 FTRN	<input type="checkbox"/> MAP		<u>B7</u>
<input type="checkbox"/> 2 FTRN	<input type="checkbox"/> FAP		<u>A3</u>
<input type="checkbox"/> APT	<input type="checkbox"/> SCAT		<u>B5</u>
<input type="checkbox"/> PERT	<input type="checkbox"/> OTHER		

PROGRAMMER COMMENTS: Comment, comment

NUMBER OF CASES     

OVER:     

OPERATOR COMMENTS:     

☐ SEE ON-LINE  
☐ SEE TECHNIQUES  
☐ MAX EXCEEDED  
☐ RETURN TO SYS  
☐ LINE MAX

OPER INIT:       
OVER:     

OUTPUT TAPES ONLY

REEL NO.	LOGIC	DEN.	UNIT	NO OF CPYS	SAVE	TAPE
	<u>B-1</u>	<u>8</u>				
	<u>B6</u>	<u>8</u>			<input checked="" type="checkbox"/>	
	<u>B5</u>	<u>8</u>			<input checked="" type="checkbox"/>	
	<u>B7</u>	<u>8</u>			<input checked="" type="checkbox"/>	
	<u>A8</u>	<u>5</u>				<input checked="" type="checkbox"/>

NO FILES 1 NO FRAMES 48 COPIES 5 DENSITY 8 COPY-FLO      KALVAR     

MSFC - Form 533 (Rev February 1966)

Figure 30 IBM 7094 Instruction Form 533

**APPENDIX**  
**Computer Program Listing**

\*\*\*\*\*I B M 7094 PROGRAM LISTING WITH JOB CARDS\*\*\*\*\*

```

$JOB          NASA JAYROE BIN 53 ,434300,00,12,14MCE
$EXECUTE      1BJOB
$IBJOB        FIOCS,MAP
$FILE         -UNIT03-,NONE
$FILE         -UNIT04-,NONE
$FILE         -UNIT07-,NONE
$FILE         -UNIT08-,NONE
$FILE         -UNIT14-,NONE
$FILE         -UNIT15-,NONE
$IBFTC ERFDP
      DIMENSION MODULE(8)
      COMMON DATA(12)
      NAMELIST/INIT/MODULE
      DO 1 I=1,8
1      MODULE(I)=0
      I=0
      READ(5,INIT)
      WRITE(6,INIT)
998    CONTINUE
      I=I+1
      IGO=MODULE(I)
      IF (IGO .LE. 0) GO TO 999
      GO TO (10,11,12,13,14,15,16),IGO
10     CONTINUE
      CALL PROB
      GO TO 998
11     CONTINUE
      CALL GLEVEL
      GO TO 998
12     CONTINUE
      CALL JONTPB
      GO TO 998
13     CONTINUE
      CALL ISOMET
      GO TO 998
14     CONTINUE
      CALL CNTLIN
      GO TO 998
15     CONTINUE
      CALL BWNDR3
      GO TO 998
16     CONTINUE
      CALL CLASFY
      GO TO 998
999    CONTINUE
      CALL CLEAN
      STOP
      END

```

\$ORIGIN ALPHA,SYSUT2,REW

```

$IBFTC MOD1
      SUBROUTINE PROB
      COMMON DATA(12)
      COMMON/C1/ GLVL(11,12),NWHICH(12)
      DIMENSION NTABLE(201,12),DATAB(201)
      NAMELIST/INPUT1/NCH,NSPS,NSCANS,NSTART,NSTOP,NBTLG,MODE,
1 ITYPE,MSFC,LTN,NSKIP,
1 NCRE,XMAX,XMIN,NOCHS,NWHICH
      READ(5,INPUT1)
      WRITE(6,INPUT1)
C      CALCULATE PROBABILITY DISTRIBUTION TABLE
      RESOL=(XMAX-XMIN)/200.0
      SCALE=200.0/(XMAX-XMIN)
C      INITIALIZE ARRAYS
      DO 6 IB=1,12
      DO 6 IBB=1,201
      NTABLE(1,IB)=0
6      CONTINUE
      DATAB(1)=XMIN
      DO 1 I=2,201
      DATAB(I)=DATAB(I-1)+RESOL
1      CONTINUE
      NFLAG=0
      DO 4 IC=1,NSCANS
      NFLAG2=1
      DO 2 I=NSTART,NSTOP,NCRE
      CALL GET1(DATA,NSPS,0,NCH,NSCANS,LTN,IERR,NFLAG2,NFLAG,NSTART,
1 NBTLG,MODE,NCRE,ITYPE,MSFC)
      GO TO (10,999,10,10,999),IERR
10     CONTINUE
      DO 3 IA=1,NOCHS
      NCHAN=NWHICH(IA)
      JJ=DATA(NCHAN)*SCALE+1.0
      IF (JJ .LT. 1) GO TO 3
      IF (JJ .GT. 201) GO TO 3
      NTABLE(JJ,NCHAN)=NTABLE(JJ,NCHAN)+1
3      CONTINUE
2      CONTINUE
4      CONTINUE
999     CONTINUE
      REWIND LTN
      WRITE(6,1000)
1000    FORMAT(1H1,50X,26HPROBABILITY DISTRIBUTION )
1001    FORMAT(1H0,130H AMPLITUDE      CH 1      CH 2      CH 3      CH 4
1      CH 5      CH 6      CH 7      CH 8      CH 9      CH 10      CH 1
21     CH 12      )
      WRITE(6,1001)
1002    FORMAT(1H ,F9.1,12I10)
      DO 5 I=1,201
      WRITE(6,1002) DATAB(I),(NTABLE(I,JJ),JJ=1,NCH)
5      CONTINUE
      CALL PRODEN(NTABLE,SCALE,GLVL,XMAX,XMIN)
20     REWIND LTN
      RETURN
      END

```

```

$IBFTC PRORZ
  SUBROUTINE PRODEFN (NTABLE,SCALE,GLVL,XMAX,XMIN )
  DIMENSION NTABLE(201,12),GLVL(11,12)
  DO 3 IM=1,12
    NTOTAL=0
    MAX=201
    DO 1 I=1,MAX
      NTOTAL=NTOTAL+NTABLE(I,IM)
1    CONTINUE
    NTEMP=0
    GLVL(1,IM)=0.0
    NCT=NTOTAL/10
    II=2
    DO 2 I=2,MAX
      IJ=I-1
      NTEMP=NTEMP+(NTABLE(IJ,IM)+NTABLE(I,IM))/2
      IF (NTEMP .LT. NCT) GO TO 2
      NTEMP=NTEMP-NCT
      GLVL(I,IM)=FLOAT(IJ)/SCALE+XMIN-.5
      II=II+1
2    CONTINUE
    GLVL(11,IM)=XMAX
3    CONTINUE
    DO 20 M=1,11
      WRITE(6,1000) (GLVL(M,MM),MM=1,12)
20   CONTINUE
1000 FORMAT(1X,12F6.1)
    RETURN
    END

```

```

$IBFTC MOD2
  SUBROUTINE GLEVEL
C
C          7094  DECK  -  MULTISPECTRAL SCANNER PLOT
C
    DIMENSION IALPHA(20)
    DIMENSION IARAY(256)
    DIMENSION IWAVE(13)
    DIMENSION NUM(20),PERCEN(20)
    DIMENSION XLIM(12)
    COMMON DATA(12)
    COMMON/C1/ GLVL(11,12),NWHICH(12)
    NAMELIST/INPUT2/NCH,NSPS,NSCANS,NSKIP,NSTART,NSTOP,ITERM,N,ICHAN,
1    IIPRT,IPLT,INCX,INCY,NSTX,NSTY,NBTLG,MODE,NCRE,LTN,IOP
    NAMELIST/GRYLVL/GLVL
    IN=5
    IN1=10
    IOUT=6
    NFLAG=0

```

```

NFLAGPT=0
RFWIND IN1
CALL CAMRAV(35)
CALL BUTTV(1)
READ(5,INPUT2)
WRITE(6,INPUT2)
DO 303 I=1,N
  XLIM(I)=GLVL(I,ICHAN)
303 CONTINUE
  READ (IN,GRYLVL)
  IF (IOPT .EQ. 0) GO TO 302
  DO 301 I=1,N
    XLIM(I)=GLVL(I,ICHAN)
301 CONTINUE
302 CONTINUE
C      *****
C      *****
  READ(IN,102)
  READ (IN,99) (IALPHA(I),I=1,N ),LLP
  READ(IN,109) XLOW,XUPP,(IWAVE(I),I=1,12)
  WRITE(IOUT,110)
1003 FORMAT(1X,12A6,16,5X,2F8.4)
300 CONTINUE
  DO 777 I=1,N
    NUM(I)=0
777 CONTINUE
    KK=N-1
    WRITE(IOUT,106)
    WRITE(IOUT,110)
    WRITE(IOUT,102)
    WRITE(IOUT,106)
    WRITE(IOUT,103) ICHAN
    DO 2 I=1,KK
      IF(I.EQ.1) GO TO 9
      WRITE (6,105) IALPHA(I),XLIM(I),XLIM(I+1)
      GO TO 2
9    WRITE(IOUT,112) (IWAVE(K),K=1, 12),IALPHA(I),XLIM(I),XLIM(I+1)
      GO TO 2
2    CONTINUE
      WRITE(IOUT,106)
      CALL LABEL1(NSTART,NSTOP,NCRE)
C
C      INUM COUNTS SCAN LINES
C
      INUM=0
      IDIF=NSTOP-NSTART+1
      IF (NSKIP .EQ. 0) GO TO 806
      DO 805 I=1,NSKIP
        NFLAG2=1
        CALL GET1(DATA,NSPS,0,NCH,NSCANO,LTN,IFRR,NFLAG2,NFLAG,NSTART,
1NBTLG,MODE,NCRF,ITYPE,MSFC)
805 CONTINUE
806 CONTINUE
      NFLAG1=0
5 CONTINUE

```



```

      IIN=0
      NFLAG2=1
205  DO 90 II=NSTART,NSTOP
      IIN=IIN+1
      CALL GET1(DATA,NSPS,      0,NCH,NSCANO,IN1,IERR,NFLAG2,NFLAG,NSTART,
1NBTLG,MODE,NCRF,ITYPE,MSFC)
      GO TO(800,801,800,800,801),IERR
801  WRITE(IOUT,100) NSCANO
      GO TO 999
800  CONTINUE
      DO 601 I=2,N
      IF (DATA(ICHAN) .GT. XLIM(I)) GO TO 601
      NUM(I-1)=NUM(I-1)+1
      IARRAY(IIN)=IALPHA(I-1)
      GO TO 90
601  CONTINUE
90   CONTINUE
      NUMTOT=INUM*IDIF
      TOTNUM=NUMTOT
      TOTPER=0.0
      DO 888 I=1,11
      XXXNUM=NUM(I)
      PERCFN(I)=(XXXNUM/TOTNUM) * 100.0
      TOTPER=TOTPER+PERCFN(I)
888  CONTINUE
96   CONTINUE
      INUM=INUM+1
      IF (IPRT .EQ. 0) GO TO 889
      WRITE(IOUT,104) NSCANO,(IARRAY(K),K=1,IDIF),LLP
889  CONTINUE
      IF (IPLT .EQ. 0) GO TO 890
      CALL PLTBF1(IARRAY,IDIF,NBLK,INCX,INCY,NSTX,NSTY,NCRE,
1NFLAGPT,NFLAG1)
890  CONTINUE
      IF (NSCANO .GE. NSCANS) GO TO 218
      GO TO 5
218  CONTINUE
      NFLAG1=0
      NFLAGPT=0
      NSCANO=0
      NSTART=NSTOP+1
      NSTOP=NSTOP+IDIF
      IF (NSTOP .GE. NSPS) NSTOP=NSPS
      ITERM=ITERM-1
      REWIND IN1
      WRITE (IOUT,110)
      WRITE (IOUT,114)
      DO 666 I=1,11
      WRITE (IOUT,115) I,NUM(I),PERCFN(I),IALPHA(I)
666  CONTINUE
      WRITE (IOUT,116) NUMTOT,TOTPER
      IF(ITERM.GT.0) GO TO 300
98   WRITE(IOUT,110)
99   FORMAT(25A1)
100  FORMAT(16I4)

```

```

101  FORMAT(12F6.1)
102  FORMAT(80H
1
103  FORMAT(2X,8HCHANNEL 12,36X,22HSYMBOL          INTERVAL /)
104  FORMAT(5X,14,1X,1H*,120A1,A1)
105  FORMAT(50X,A1,8X,F6.1,3H - ,F6.1)
106  FORMAT(1X/)
108  FORMAT(10X,115A1)
109  FORMAT(2F10.0,12A1)
110  FORMAT(1H1/)
111  FORMAT(2X,83HCROPS  C5-17,5-22,5-5,5-8,          ALTITUDE 2000 FT.
1
      DATE RECORDED 6/30/66 //)
112  FORMAT(2X,23HWAVE LENGTH (MICRONS)  ,12A1,13X,A1,8X,F6.1,
      13H - ,F6.1)
113  FORMAT(11X,112A1)
114  FORMAT(20X,5HCLASS,7X,13HSAMPLE NUMBER,6X,7HPERCENT,10X,
      112HALPHA SYMBOL/)
115  FORMAT (21X,12,10X,16,12X,F7.2,15X,A1)
116  FORMAT (20X,5HTOTAL, 8X,16,12X,F7.2)
117  FORMAT (314,12F7.3)
999  CONTINUE
      REWIND IN1
      RETURN
      END

```

#### \$IBFTC PLOTT1

```

      SUBROUTINE LABEL1(NSTART,NSTOP,INCRE          )
      DIMENSION IOUT(120),JOUT(120),KOUT(120),LOUT(120)
      NDIF=(NSTOP-NSTART+1)/INCRE
      II=0
      DO 1 I=NSTART,NSTOP,INCRE
      II=II+1
      IOUT(II)=I/1000
      JOUT(II)=I/100-I/1000*10
      KOUT(II)=I/10-I/100*10
      LOUT(II)=I-I/10*10
      IF (LOUT(II) .LE. 0) LOUT(II)=0
1
      CONTINUE
      WRITE (6,10) (IOUT(I),I=1,NDIF)
      WRITE (6,10) (JOUT(I),I=1,NDIF)
      WRITE (6,10) (KOUT(I),I=1,NDIF)
      WRITE (6,10) (LOUT(I),I=1,NDIF)
10
      FORMAT (11X,120I1)
      RETURN
      END

```

#### \$IBFTC PLLTT1

```

      SUBROUTINE PLTRF1(ISYM,NN,NSQR,INCX,INCY,NSTX,NSTY,NCRF,
      1NFLAG,NFLAG1)
      DIMENSION ISYM(1),NRAUFER(50)
      IF (NFLAG .NE. 0) GO TO 10
      NSQR=1024/1ABS(INCY+INCX)
10
      CONTINUE

```

```

IF (NFLAG1 .NE. 0) GO TO 20
CALL FRAMEV(0)
NCOUNT=0
INCRX=NSTX
INCRY=NSTY
NFLAG1=1
IF (NFLAG .EQ. 0) GO TO 11
CALL APRNTV (INCX, INCY, NN, NBUFER, INCRX, INCRY)
INCRY=INCRY+INCX
INCRX=INCRX+IABS(INCY)
11  NFLAG=1
20  CONTINUE
    NCOUNT=NCOUNT+1
    DO 1 I=1,50
      NBUFER(I)=0
1    CONTINUE
      IA=0
      DO 2 I=1,NN
        IB=IA+6
        IC=IB/6
        ID=IB-IC*6
        IE=ID*6
        IA=IA+1
        CALL FLD(NBUFER(IC), IF, 6, 0, ISYM(I))
2    CONTINUE
      CALL APRNTV(INCX, INCY, NN, NBUFER, INCRX, INCRY)
      INCRY=INCRY+INCX
      INCRX=INCRX+IABS(INCY)
      IF (NCOUNT .GE. NSQR) NFLAG1=0
      RETURN
END

```

```

$IBFTC GETDA1
SUBROUTINE GET1(DATA, NSPS, NSKIP, NCPW, NSCANO, IRW, IERR, NFLAG2,
1 NFLAG,
1 NSTART, NBTLG, MODE, NCRE, ITYPE, MSFC )
  DIMENSION DATA(1), NDAT(890)
  DATA NFLAG/0/
  IF (NFLAG .NE. 0) GO TO 12
  NTEMP=NCPW*(NCRE-1)
  NSCANO=0
  NL=36-NBTLG
  NBLNG=36/NBTLG
  NFLAG=1
  NSTMP=(NSPS+NSTART-1)*NCPW+MSFC*19
  NSCANS=NSTMP
  NTMP=NSTMP/NBLNG
  NSTMP=NSTMP/NBLNG*NRLNG
  IF (NSTMP .LT. NSCANS) NTMP=NTMP+1
  NSCANS=NTMP
  IF (NSKIP .EQ. 0) GO TO 402
  DO 401 I=1,NSKIP
    NSCANO=NSCANO+1
    CALL SKRBIN (IRW, 1, RD )

```

```

401 CONTINUE
402 CONTINUE
12 CONTINUE
   IF (NFLAG2 .EQ. 0) GO TO 10
13 CONTINUE
   M=(NSTART-1)*NCPW+MSFC*19
   IF (MODE .EQ. 1) GO TO 50
   CALL RENTPR (IRW,MODE,IFRR,NW,NSCANS,NDAT)
   GO TO 51
50 CALL RENTPC (IRW,MODE,IFRR,NW,NSCANS,NDAT)
51 CONTINUE
1000 FORMAT (1X,I6)
   NNW=NW*6
   NFLAG2=0
   NSCANO=NSCANO+1
10 CONTINUE
   DO 14 NN=1,NCPW
   IB=M+NBLNG
   ID=IR/NBLNG
   IF=IB-NBLNG*ID
   IBIT=NBTLG*IF
   M=M+1
   IF (ITYPE .EQ. 1) GO TO 15
   NDATA=0
   CALL FLD(NDATA,NL,NBTLG,IBIT,NDAT(ID))
   DATA(NN)=NDATA
   GO TO 14
15 CONTINUE
   DATAN=0.0
   CALL FLD(DATAN,NL,NBTLG,IBIT,NDAT(ID))
   DATA(NN)=DATAN
14 CONTINUE
   M=M+NTEMP
   RETURN
   END

```

\$ORIGIN ALPHA,SYSUT2,REW

\$IBFTC MOD3

```

SUBROUTINE JONTPB
  DIMENSION NKNT(4000),NP(4000,2),NWKCD( 750),NWKCL( 750)
  DIMENSION DATA(12)
C  DIMENSION IBIN( 750)
  DIMENSION ALPNUM(47),ALPHA(120),CORDX(3)
  DIMENSION IMX(6),IMY(6)
  NAMELIST /INPUT3/ NCH,NSPS,NSCANS,NSKIP,NSTART,NSTOP,LTN,NBTLG,
1  MODE,ITYPE,MSFC,NCRE,NOJP,IMX,IMY,SCALE,BIAS
  DATA ASTRIK/1H*/
  DATA XMARK/1HX/
  DATA BLANK/6H /
1060 FORMAT(48X,25HDATA SWITCH HAS OCCURRED )
1061 FORMAT(49X,30HJOINT PROBABILITY DISTRIBUTION )

```

```

1062 FORMAT(1H1)
1063 FORMAT(44X,11H X-AXIS IS ,I6,6X,11H Y-AXIS IS ,I6)
1040 FORMAT(1H ,67H MAXIMUM PROBABILITY OF UNCOMMONALITY EXCEEDED- CONT
11NUE EXCUTION ,I6)
1064 FORMAT(1X,26HSYMBOL N/SYMBOL )
1065 FORMAT(11X,121(1H*),/,11X,1H*,55X,5HPART ,I1,4H OF ,I1,53X,1H*,/
1,11X,121(1H*))
IRT=11
NFLG3=0
LIMIT=4000
READ(5,INPUT3)
WRITE(6,INPUT3)
READ(5,1000) (ALPNUM(I),I=1,47)
1000 FORMAT(1X,47A1)
C REWIND IRT
DO 80 NTIME=1,NOJP
NFLG=0
NH=1
NV=2
IF (NSKIP .EQ. 0) GO TO 9
DO 8 I=1,NSKIP
CALL SKRBIN(LTN,1,RD)
8 CONTINUE
9 CONTINUE
MIX=IMX(NTIME)
MIY=IMY(NTIME)
DO 10 I=1,4000
10 NKNT(I)=1
WRITE (6,1062)
WRITE(6,1061)
WRITE(6,1063) MIX,MIY
NCLS=1
DO 13 MRP=1,NSCANS
NFLAG2=1
DO 15 MPR=1,NSPS
IF (NFLG3 .GT. 0) GO TO 16
CALL GET2(DATA,NSPS,0,NCH,NSCANO,LTN,IERR,NFLAG2,NSTART,
1NBTLG,MODE,NCRF,ITYPE,MSFC)
NC=DATA(MIX)*SCALE+BIAS
NR=DATA(MIY)*SCALE+BIAS
IF (NC .LT. 1) NC=1
IF (NC .GT. 255) NC=255
IF (NR .LT. 1) NR=1
IF (NR .GT. 255) NR=255
NP(1,NH)=NC
NP(1,NV)=NR
NFLG3=1
GO TO 15
16 CONTINUE
CALL GET2(DATA,NSPS,0,NCH,NSCANO,LTN,IERR,NFLAG2,NSTART,
1NBTLG,MODE,NCRF,ITYPE,MSFC)
GO TO (996,999,998,996,999),IERR
999 WRITE(6,1070) NSCANO
1070 FORMAT(33HEND-OF-FILE ON INPUT AT SCAN NO. ,I6)
GO TO 995

```

```

998 WRITE(6,1071)
1071 FORMAT(27HIRRECOVERABLE PARITY ERROR )
GO TO 995
996 CONTINUE
NC=DATA(MIX)*SCALE+BIAS
NR=DATA(MIY)*SCALE+BIAS
IF (NC .LT. 1) NC=1
IF (NC .GT. 255) NC=255
IF (NR .LT. 1) NR=1
IF (NR .GT. 255) NR=255
DO 11 I=1,NCLS
IF (NC .NE. NP(I,NH)) GO TO 11
IF (NR .NE. NP(I,NV)) GO TO 11
NKNT(I)=NKNT(I)+1
GO TO 15
11 CONTINUE
IF (NCLS .GE. LIMIT) GO TO 15
NCLS=NCLS+1
NP(NCLS,NH)=NC
NP(NCLS,NV)=NR
15 CONTINUE
13 CONTINUE
17 CONTINUE
1020 FORMAT (1X,3I6)
C FIND MINIMUM AND MAXIMUM IN ROW AND COLUMN DATA
MINC=NP(1,NH)
MAXC=NP(1,NH)
MINR=NP(1,NV)
MAXR=NP(1,NV)
DO 25 I=1, NCLS
IF (NP(I,NH) .GT. MAXC) MAXC=NP(I,NH)
IF (NP(I,NV) .GT. MAXR) MAXR=NP(I,NV)
IF (NP(I,NH) .LT. MINC) MINC=NP(I,NH)
IF (NP(I,NV) .LT. MINR) MINR=NP(I,NV)
25 CONTINUE
C TEST FOR SPREAD
NDIFV=MAXR-MINR+1
NDIFH=MAXC-MINC+1
IF (NDIFV .GE. NDIFH) GO TO 19
WRITE(6,1060)
WRITE(6,1063) MIY,MIX
NH=2
NV=1
NTEMP=MAXC
MAXC=MAXR
MAXR=NTEMP
NTEMP=MINC
MINC=MINR
MINR=NTEMP
NTEMP=NDIFH
NDIFH=NDIFV
NDIFV=NTEMP
19 CONTINUE
WRITE(6,1064)
C ORDER ROW DATA IN DECENDING ORDER

```

```

C      BUBBLE-UP
      NSORT=NCLS
21     CONTINUE
      DO 20 I=2,NSORT
      IF (NP(I-1,NV) .GE. NP(I,NV)) GO TO 20
      NTEMP1=NP(I-1,NV)
      NTEMP2=NP(I-1,NH)
      NTEMP3=NKNT(I-1)
      NP(I-1,NV)=NP(I,NV)
      NP(I-1,NH)=NP(I,NH)
      NKNT(I-1)=NKNT(I)
      NP(I,NV)=NTEMP1
      NP(I,NH)=NTEMP2
      NKNT(I)=NTEMP3
20     CONTINUE
      NSORT=NSORT-1
      IF (NSORT .GT. 1) GO TO 21
C      CALCULATE TABLE
      MAXKNT=0
      DO 22 I=1,NCLS
22     IF (NKNT(I) .GT. MAXKNT) MAXKNT=NKNT(I)
      NFACT=MAXKNT/45
      XXX=FLOAT(MAXKNT)/46.0
      NFAC=0
      IF (NFACT .LT. 1) NFACT=1
      WRITE(6,1050) BLANK,NFAC
      NFAC=NFAC+NFACT
      DO 23 I=1,46
      WRITE(6,1050) ALPNUM(I),NFAC
1050    FORMAT (3X,A6,6X,I6)
      NFAC=NFAC+NFACT
23     CONTINUE
      GO TO 18
14     CONTINUE
      WRITE(6,1040) LIMIT
      GO TO 17
18     CONTINUE
C      PRINT DISTRIBUTION ON PAGE
C      SET UP LOOP
      ITERM=1
      IF (NDIFH .EQ. 120) GO TO 40
      ITERM=NDIFH/120+1
40     CONTINUE
      NST=1
      NSO=NST+119
      IF (NSO .GT. NDIFH) NSO=NDIFH
      DO 50 LOOP=1,ITERM
      WRITE(6,1065) LOOP,ITERM
      CORDX(1)=FLOAT(NST+MINC-2)
      CORDX(2)=CORDX(1)+60.0
      CORDX(3)=CORDX(1)+110.0
1021    FORMAT (1H1)
      IB=1
      DO 60 II=1,NDIFV
      DO 66 I=1,120

```

```

        ALPHA(I)=BLANK
66      CONTINUE
C      IF (NFLG .EQ. 1) GO TO 69
C      DO 68 I=1,NDIFH
C      IBIN(I)=0
C68     CONTINUE
C69     CONTINUE
        IF (NP(IB,NV) .NE. MAXR-II+1) GO TO 65
        IA=0
        DO 26 I=IB,NCLS
        IE=I
        IF (NP(I,NV) .NE. NP(IB,NV)) GO TO 31
        IA=IA+1
        NWKCD(IA)=NP(I,NH)
        NWKCL(IA)=NKNT(I)
26      CONTINUE
31      CONTINUE
        IB=IE
C      ORDER X-AXIS
        NSORT=IA
        NUMCLX=IA
        IF (IA .LE. 1) GO TO 30
28      CONTINUE
        DO 27 IC=2,NSORT
        IF (NWKCD(IC-1) .LE. NWKCD(IC)) GO TO 27
        NTEMP1=NWKCD(IC-1)
        NTEMP2=NWKCL(IC-1)
        NWKCD(IC-1)=NWKCD(IC)
        NWKCL(IC-1)=NWKCL(IC)
        NWKCD(IC)=NTEMP1
        NWKCL(IC)=NTEMP2
27      CONTINUE
        NSORT=NSORT-1
        IF (NSORT .GE. 2) GO TO 28
1030   FORMAT(1X,2I6)
30      CONTINUE
C      IF (NFLG .EQ. 1) GO TO 91
C      IM=1
C      DO 90 I=1,NDIFH
C      IF (NWKCD(IM) .NE. 1) GO TO 90
C      IBIN(I)=NWKCL(IM)
C      IM=IM+1
C90     CONTINUE
C91     CONTINUE
        NMJ=NST+MINC-1
        DO 67 ID=1,NUMCLX
        IF (NWKCD(ID) .LT. NMJ) GO TO 67
        IC=ID
        GO TO 29
67      CONTINUE
29      CONTINUE
        IA=0
        DO 64 I=NST,NSO
        IA=IA+1
        IF (NWKCD(IC) .NE. MINC+I-1) GO TO 64

```



```

        XX=FLOAT(NWKCL(IC))/XXX
        ICAR=XX+(1.001-1.0/XXX)
        ALPHA(IA)=ALPNUM(ICAR)
        IC=IC+1
64      CONTINUE
65      CONTINUE
        IF (NFLG .EQ. 1) GO TO 70
C      WRITE(IRT) (IBIN(I),I=1,NDIFH)
70      CONTINUE
        CORDY=FLOAT(MAXR-II+1)
        YMARG=XMARK
        IF (NDIFV-II .NE. (NDIFV-1-II/10*10)) YMARG=ASTRIK
        WRITE(6,1008) CORDY,YMARG,(ALPHA(I),I=1,120)
1008    FORMAT(1X,F8.1,2X,A1,120A1)
60      CONTINUE
        NST=NSO+1
        NSO=NST+119
        IF (NSO .GT. NDIFH) NSO=NDIFH
        WRITE(6,1010)
        WRITE(6,1011) CORDX(1),CORDX(2),CORDX(3)
1011    FORMAT (6X,F10.4,50X,F10.4,40X,F10.4)
        NFLG=1
        WRITE(6,1062)
50      CONTINUE
        REWIND LTN
C      END FILE IRT
80      CONTINUE
C      REWIND IRT
995     CONTINUE
1010    FORMAT (11X,12(10HX*****))
        RETURN
        END

```

```

$IBFTC GETDA2
        SUBROUTINE GET2(DATA,NSPS,NSKIP,NCPW,NSCANO,IRW,IERR,NFLAG2,
1        INSTART,NBTLG,MODE,NCRE,ITYPE,MSFC )
        DIMENSION DATA(1),NDAT(890)
        DATA NFLAG/0/
        IF (NFLAG .NE. 0 ) GO TO 12
        NTEMP=NCPW*(NCRE-1)
        NSCANO=0
        NL=36-NBTLG
        NBLNG=36/NBTLG
        NFLAG=1
        NSTMP=(NSPS+NSTART-1)*NCPW+MSFC*19
        NSCANS=NSTMP
        NTMP=NSTMP/NBLNG
        NSTMP=NSTMP/NBLNG*NBLNG
        IF (NSTMP .LT. NSCANS) NTMP=NTMP+1
        NSCANS=NTMP
        IF (NSKIP .EQ. 0) GO TO 402
        DO 401 I=1,NSKIP
        NSCANO=NSCANO+1
        CALL SKRBIN (IRW,1,RD )

```

```

401 CONTINUE
402 CONTINUE
12 CONTINUE
   IF (NFLAG2 .EQ. 0) GO TO 10
13 CONTINUE
   M=(NSTART-1)*NCPW+MSFC*19
   IF (MODE .EQ. 1) GO TO 50
   CALL REDTPR (IRW,MODE,IERR,NW,NSCANS,NDAT)
   GO TO 51
50 CALL REDTPC (IRW,MODE,IERR,NW,NSCANS,NDAT)
51 CONTINUE
1000 FORMAT (1X,I6)
   NNW=NW*6
   NFLAG2=0
   NSCANO=NSCANO+1
10 CONTINUE
   DO 14 NN=1,NCPW
   IB=M+NBLNG
   ID=IB/NBLNG
   IF=IB-NBLNG*ID
   IBIT=NBTLG*IF
   M=M+1
   IF (ITYPF .EQ. 1) GO TO 15
   NDATA=0
   CALL FLD(NDATA,NL,NBTLG,IBIT,NDAT(ID))
   DATA(NN)=NDATA
   GO TO 14
15 CONTINUE
   DATAN=0.0
   CALL FLD(DATAN,NL,NBTLG,IBIT,NDAT(ID))
   DATA(NN)=DATAN
14 CONTINUE
   M=M+NTEMP
   RETURN
END

```

\$ORIGIN ALPHA,SYSUT2,REW

\$IBFTC MOD4

```

SUBROUTINE ISOMET
  DIMENSION NTA(256),NTB(256), DATA(256),TIME(256),DAT(12)
  DIMENSION NTC(256),NTD(256)
  NAMELIST/INPUT4/ NCH,NSPS,NSKIP,NBTLG,MODE,IRW,NCHAN,NSNCRE,NPCRE,
  1ITYPE,MSFC,
  2NPTSL,NPTSU,
  1MAXSCN,XMIN,XMAX,YMIN,YMAX,NBLSZX,NBLSZY,NSECT,NSMOV
  2,NDIREC
  READ (5,INPUT4)
  WRITE(6,INPUT4)
  NUP=512/NBLSZY
  NBLDIR=NBLSZX*NDIREC
  NTIMES=MAXSCN/NUP
  CALL CAMRAV(9)
  NBACK=1

```

```

      IF (NSKIP .EQ. 0) GO TO 33
      DO 32 I=1,NSKIP
      NFLAG2=1
      CALL GET3(DAT,NSPS,0,NCH,NSCANO,IRW,IERR,NFLAG2,NPTSL,NBTLG,
12      ,NPCRE,ITYPE,MSFC)
32  CONTINUE
33  CONTINUE
      DO 18 MMRR=1,NSECT
      NPTSUU=NPTSU
      XMIN=FLOAT(NPTSL)
      XMAX=FLOAT(NPTSUU)
      NDIFF=NPTSUU-NPTSL+1
      IF (NSMOV .NE. 0) NPTSUM=NDIFF -NSMOV+1
      NFLAG=0
      DO 16 MPR=1,NTIMES
      IF (NDIREC) 23,24,24
24  IXR=512-(512/NBLSZX-NUP)*NBLSZX
      IXL=0
      GO TO 25
23  IXL=512-(512/NBLSZX-NUP)*NBLSZX
      IXR=0
25  CONTINUE
      IYB=512
      IYT=0
      CALL FRAMEV(0)
      DO 10 MRP=1,NUP
      DO 17 MMRP=1,NSNCRE
      NFLAG2=1
      CALL GET3(DAT,NSPS,0,NCH,NSCANO,IRW,IERR,NFLAG2,NPTSL,NBTLG,
1MODE,NPCRE,ITYPE,MSFC)
      IF (NFLAG .EQ. 0) GO TO 19
17  CONTINUE
19  CONTINUE
      NFLAG=1
      DATA(1)=DAT(NCHAN)
      DO 1 I=2,NDIFF
      CALL GET3(DAT,NSPS,0,NCH,NSCANO,IRW,IERR,NFLAG2,NPTSL,NBTLG,
1MODE,NPCRE,ITYPE,MSFC)
      DATA(I)=DAT(NCHAN)
1  CONTINUE
      IF (NSMOV .EQ. 0) GO TO 22
      DO 20 I=1      ,NPTSUM
      IA=I
      IB=IA+NSMOV-1
      TEMP=0.0
      DO 21 II=1A+IB
      TEMP=TEMP+DATA(II)
21  CONTINUE
      TEMP=TEMP/FLOAT(NSMOV)
      DATA(I)=TEMP
20  CONTINUE
22  CONTINUE
      CALL SETMIV (IXL,IXR,IYB,IYT)
      CALL XSCALV (XMIN,XMAX,IXL,IXR)
      CALL YSCALV (YMIN,YMAX,IYB,IYT)

```

```

DO 11 I=1,NDIFF
TIME(I)=FLOAT(NPTSL-1+I)
NTA(I)=NYV(DATA(I))
NTR(I)=NXV(TIME(I))
11 CONTINUE
DO 12 I=2,NDIFF
CALL LINEV (NTR(I-1),NTA(I-1),NTB(I),NTA(I))
12 CONTINUE
IF (MRP .LE. 1) GO TO 15
DO 13 I=1,NDIFF
CALL LINEV (NTD(I),NTC(I),NTB(I),NTA(I))
13 CONTINUE
15 CONTINUE
DO 14 I=1,NDIFF
NTD(I)=NTR(I)
NTC(I)=NTA(I)
14 CONTINUE
IXL=IXL+NBLDIR
IXR=IXR-NBLDIR
IYB=IYB-NBLSZY
IYT=IYT+NBLSZY
10 CONTINUE
CALL BSRECD(IRW,NBACK,NOF)
16 CONTINUE
REWIND IRW
IF (NSKIP .EQ. 0) GO TO 30
DO 31 I=1,NSKIP
NFLAG2=1
CALL GET3(DAT,NSPS,0,NCH,NSCANO,IRW,IERR,NFLAG2,NPTSL,NBTLG,
1MODE,NPCRE,ITYPE,MSFC)
31 CONTINUE
30 CONTINUE
NPTSU=NPTSUU
NTEMP=NPTSL
NPTSL=NPTSU+1
NPTSU=NPTSU+(NPTSU-NTEMP)+1
18 CONTINUE
RETURN
END

```

```

$IBFTC GETDA3
SUBROUTINE GET3(DATA,NSPS,NSKIP,NCPW,NSCANO,IRW,IERR,NFLAG2,
1NSTART,NBTLG,MODE,NCRE,ITYPE,MSFC)
DIMENSION DATA(1),NDAT(890)
DATA NFLAG/0/
IF (NFLAG .NE. 0) GO TO 12
NTEMP=(NCRE-1)*NCPW
NSCANO=0
NL=36-NBTLG
NBLNG=36/NBTLG
NFLAG=1
NSTMP=(NSPS+NSTART-1)*NCPW+MSFC*19
NSCANS=NSTMP
NTEMP=NSTMP/NBLNG

```

```

NSTMP=NSTMP/NBLNG*NBLNG
IF (NSTMP .LT. NSCANS) NTMP=NTMP+1
NSCANS=NTMP
IF (NSKIP .EQ. 0) GO TO 402
DO 401 I=1,NSKIP
NSCANO=NSCANO+1
CALL SKR BIN (IRW,1,RD )
401 CONTINUE
402 CONTINUE
12 CONTINUE
IF (NFLAG2 .EQ. 0) GO TO 10
13 CONTINUE
M=(NSTART-1)*NCPW+MSFC*19
IF (MODE .EQ. 1) GO TO 50
CALL REDTPR (IRW,MODE,IERR,NW,NSCANS,NDAT)
GO TO 51
50 CALL REDTPC (IRW,MODE,IERR,NW,NSCANS,NDAT)
51 CONTINUE
1000 FORMAT (1X,I6)
NNW=NW*6
NFLAG2=0
NSCANO=NSCANO+1
10 CONTINUE
DO 14 NN=1,NCPW
IB=M+NBLNG
ID=IB/NBLNG
IF=IB-NBLNG*ID
IBIT=NBTLG*IF
M=M+1
IF (ITYPE .EQ. 1) GO TO 15
NDATA=0
CALL FLD(NDATA,NL,NBTLG,IBIT,NDAT(ID))
DATA(NN)=NDATA
GO TO 14
15 CONTINUE
DATAN=0.0
CALL FLD(DATAN,NL,NBTLG,IBIT,NDAT(ID))
DATA(NN)=DATAN
14 CONTINUE
M=M+NTMP
RETURN
END

```

```

$ORIGIN      ALPHA,SYSUT2,REW
$IBFTC MOD5
SUBROUTINE CNTLIN
DIMENSION DAT(12)
COMMON /LAB /NI3,NF3,NT3,Z(2560),KON(3400),NI2,NF2,NT2,U(3400),
1V(3400)

```

```

    NAMELIST /INPUT5/ NCH,NSPS,IRW,NCHAN,NSNCRE,NPCRE,NPTSL,NPTSU,
    2NBTLG,MODE,
    21TYPE,MSFC,
    1NSKIP,
    1MAXSCN,NSECT, MSZX, MSZY, BLK,FHINC,ZMIN,ZMAX,LAR
    READ (5,INPUT5)
    WRITE (6,INPUT5)
    CALL OPEN (IRW,1)
    IXR=1024.0-BLK+.5
    IXL=0
    IYR=0
    IYT=136
    NCRE=NPCRE
    NBLLK=1024.0/BLK+.5
    XNBLK= BLK
    FNPTSL=NPTSL
    FNPTSU=NPTSU
    NUP=MAXSCN/ ((MSZY-1)*NSNCRE)
    NSECT=NSPS/ MSZX
    NDIF=(NPTSU-NPTSL+1)/NPCRE
    NFLAG1=0
    FDIF=NDIF
    FRM= MSZY
    CALL CAMRAV( 35)
    NWDS=NCH*NSPS
    CALL BUTTV(1)
    CALL SETMIV(IXL,IXR,IYR,IYT)
    IF (NSKIP .EQ. 0) GO TO 25
    DO 26 I=1,NSKIP
    NFLAG2=1
    CALL GET5(DAT,NSPS ,0,NCH,NSCANO,IRW,IERR,NFLAG2,NPTSL,
    1NBTLG,MODE,NPCRE,1TYPE,MSFC)
26  CONTINUE
25  CONTINUE
C  READ(IRW)
    III=0
    CALL FRAMEV(0)
    DO 18 MMRR=1,NSECT
    NPLTMP=NPTSL+1
    NPTSUU=NPTSU
    NPTSU=NPTSU-NPCRE
    NFLAG=0
    IMM=0
    DO 16 MRPP=1,NUP
    III=III+1
    IF (III .LE. NBLLK) GO TO 21
    CALL FRAMEV(0)
    III=1
    IXR=1024.0-BLK+.5
    IXL=0
21  CONTINUE
    CALL YSCALV(1.0 ,FDIF ,IYR,IYT)
    CALL XSCALV(1.0,FRM,IXL,IXR)
    DO 10 MRP=1, MSZY
    IF (NFLAG1 .NE. 1) GO TO 20

```

```

DO 22 IIM=1,NDIF
  IMM=IMM+1
  IMI=IMI+1
  Z(IIM)=Z(IMI)
22  CONTINUE
  NFLAG1=0
  GO TO 10
20  CONTINUE
  DO 17 MMRP=1,NSNCRE
    NFLAG2=1
1001 FORMAT(1X,16F4.1)
    CALL GET5(DAT,NSPS ,0,NCH,NSCANO,IRW,IERR,NFLAG2,NPTSL,
1NBTLG,MODE,NPCRE,ITYPE,MSFC)
    IF (NFLAG .EQ. 0) GO TO 19
17  CONTINUE
19  CONTINUE
    NFLAG=1
    IMM=IMM+1
    Z(IIM)=DAT(NCHAN)
    DO 1 I=NPLTMP,NPTSUU,NPCRE
      IMM=IMM+1
      CALL GET5(DAT,NSPS ,0,NCH,NSCANO,IRW,IERR,NFLAG2,NPTSL,
1NBTLG,MODE,NPCRE,ITYPE,MSFC)
      Z(IIM)=DAT(NCHAN)
1  CONTINUE
10  CONTINUE
1000 FORMAT (1X,10F10.2)
    CALL CONTOR(MSZY,NDIF,FHINC,LAB,FNPTSL,FNPTSU,FRM,ZMIN,ZMAX)
    IXL=FLOAT(IXL)+BLK+.5
    IXR=FLOAT(IXR)-BLK+.5
    CALL SETMIV (IXL,IXR,IYB,IYT)
    IMM=0
    IMI=(MSZY-1)*NDIF
    NFLAG1=1
16  CONTINUE
C   REWIND IRW
C   READ (IRW)
    NPTSU=NPTSUU
    NTEMP=NPTSL
    NPTSL=NPTSU-NPCRE
    NPTSU=NPTSU+(NPTSU-NTEMP)-NPCRE
18  CONTINUE
    STOP
    END
$IRFTC GETDA5
  SUBROUTINE GET5(DATA,NSPS,NSKIP,NCPW,NSCANO,IRW,IERR,NFLAG2,
1NSTART,NBTLG,MODE,NCRE,ITYPE,MSFC)
    DIMENSION DATA(1),NDAT( 890)
    DATA NFLAG/0/
    IF (NFLAG .NE. 0 ) GO TO 12
    NTEMP=(NCRE-1)*NCPW
    NSCANO=0
    NL=36-NBTLG
    NBLNG=36/NBTLG
    NFLAG=1

```

```

NSTMP=(NSPS+NSTART-1)*NCPW+MSFC*19
NSCANS=NSTMP
NTMP=NSTMP/NBLNG
NSTMP=NSTMP/NBLNG*NBLNG
IF (NSTMP .LT. NSCANS) NTMP=NTMP+1
NSCANS=NTMP
IF (NSKIP .EQ. 0) GO TO 402
DO 401 I=1,NSKIP
NSCANO=NSCANO+1
CALL SKRBIN (IRW,1,RD )
401 CONTINUE
402 CONTINUE
12 CONTINUE
IF (NFLAG2 .EQ. 0) GO TO 10
13 CONTINUE
M=(NSTART-1)*NCPW+MSFC*19
IF (MODE .EQ. 1) GO TO 50
CALL REDTPR (IRW,MODE,IERR,NW,NSCANS,NDAT)
GO TO 51
50 CALL REDTPC (IRW,MODE,IERR,NW,NSCANS,NDAT)
51 CONTINUE
1000 FORMAT (1X,I6)
NNW=NW*6
NFLAG2=0
NSCANO=NSCANO+1
10 CONTINUE
DO 14 NN=1,NCPW
IB=M+NBLNG
ID=IR/NBLNG
IF=IR-NBLNG*ID
IBIT=NBTLG*IF
M=M+1
IF (ITYPE .EQ. 1) GO TO 15
NDATA=0
CALL FLD(NDATA,NL,NBTLG,IBIT,NDAT(ID))
DATA(NN)=NDATA
GO TO 14
15 CONTINUE
DATAN=0.0
CALL FLD(DATAN,NL,NBTLG,IBIT,NDAT(ID))
DATA(NN)=DATAN
14 CONTINUE
M=M+NTMP
RETURN
END

```

\$IBFTC CTOR

```

SUBROUTINE CONTOR(L,M,FHINC,LAB,FNPTSL,FNPTSU,FRM,ZMIN,ZMAX)
DIMENSION I(5),V1(3),V2(3),P1(3),P2(3),X(5),Y(5)
DIMENSION V3(3)
COMMON /LAB /N13,NF3,NT3,Z(2560),KON(3400),N12,NF2,NT2,U(3400),
1V(3400)
LOGICAL JCODE
IF (M.GT.0.AND.L.GT.0.AND.FHINC.GT.0.0.AND.LAB.GE.0) GO TO 1

```



```

WRITE (6,101) M,L,FHINC
RETURN
1  N=3400
   NC=(ZMAX-ZMIN)/ABS(FHINC)
   FH=ZMIN
2  CONTINUE
   NLAB=LAB-1
   IF (LAB .EQ. 0) NLAB=LAB+1
   DO 15 IH=1,NC
     NI2=6
     NF2=5
     NT2=5
     V(2)=FNPTSU
     U(2)=FRM
     V(4)=FNPTSL
     U(4)=1.0
     K=1
     NLAB=NLAB+1
     IF (NLAB .NE. LAB) GO TO 51
     K=2
     NLAB=0
51  DO 10 IL=2,L
     DO 10 IM=2,M
       I(3)=(IL-1)*M+IM
       I(2)=I(3)-1
       I(4)=I(3)-M
       I(1)=I(4)-1
       I(5)=I(1)
       X(1)=IM-1
       X(2)=IM-1
       X(3)=IM
       X(4)=IM
       X(5)=IM-1
       Y(1)=IL-1
       Y(2)=IL
       Y(3)=IL
       Y(4)=IL-1
       Y(5)=IL-1
       IZ2=I(2)
       IZ1=I(1)
       IZ3=I(3)
       IZ4=I(4)
       IZ5=I(5)
1000 FORMAT (1X,2F10.2,16)
      V1(1)=(X(1)+X(4))/2.0
      V1(2)=(Y(1)+Y(2))/2.0
      V1(3)=(Z(IZ1)+Z(IZ2)+Z(IZ3)+Z(IZ4))/4.0
      DO 4 J=1,4
        IZ=I(J)
        V2(1)=X(J)
        V2(2)=Y(J)
        V2(3)=Z(IZ)
        IZ=I(J+1)
        V3(1)=X(J+1)
        V3(2)=Y(J+1)

```

```

      V3(3)=Z(1Z)
      IF (V2(3) .LE. 0.0 .AND. V3(3) .LE. 0.0) GO TO 4
      NV2=V2(3)+.5
      NV3=V3(3)+.5
      IF (NV2 .EQ. NV3) GO TO 4
1002  FORMAT(1X,3F10.2)
      CALL STRIKE(V1,V2,V3,FH,P1,P2,IER)
      IF (IER .NE. 2) GO TO 4
      IF (NF2+2 .LE. N) GO TO 59
      WRITE (6,100) FH,N
      GO TO 60
59    NF2=NF2+2
      U(NF2-1)=P1(2)
      V(NF2-1)=P1(1)
      KON(NF2-1)=0
      U(NF2)=P2(2)
      V(NF2)=P2(1)
      KON(NF2)=1
4     CONTINUE
10    CONTINUE
60    IF (NI2 .GE. NF2) GO TO 15
      JCODE=.TRUE.
      DO 61 J=NI2,NF2
      JTEMP=J
      DO 61 JJ=2,4,2
      IF (U(J) .EQ. U(JJ)) GO TO 68
      IF (V(J) .EQ. V(JJ)) GO TO 68
61    CONTINUE
      NT2=NT2+2
      U(NT2-1)=U(NI2)
      V(NT2-1)=V(NI2)
      KON(NT2-1)=0
      U(NT2)=U(NI2+1)
      V(NT2)=V(NI2+1)
      KON(NI2)=1
      NI2=NI2+2
      GO TO 70
68    J=JTEMP
      IF (KON(J) .EQ. 0) GO TO 62
      JJ=J-1
      JMAX=J
      GO TO 63
62    JJ=J+1
      JMAX=JJ
63    V1(1)=U(J)
      V1(2)=V(J)
      V2(1)=U(JJ)
      V2(2)=V(JJ)
      JDIF=JMAX-NI2-1
      DO 64 JSUB=1,JDIF
      JDEX=JMAX-JSUB+1
      KDEX=JMAX-JSUB-1
      U(JDEX)=U(KDEX)
64    V(JDEX)=V(KDEX)
      NI2=NI2+2

```

```

      IF (JCONF) GO TO 72
      NT2=NT2+1
      U(NT2)=V2(1)
      V(NT2)=V2(2)
      KON(NT2)=1
      GO TO 70
72    NT2=NT2+2
      U(NT2-1)=V1(1)
      V(NT2-1)=V1(2)
      KON(NT2-1)=0
      U(NT2)=V2(1)
      V(NT2)=V2(2)
      KON(NT2)=1
70    IF (NI2 .GE. NF2) GO TO 16
      DO 71 J=NI2,NF2
      JTEMP=J
      IF (U(J).NE.U(NT2).OR.V(J).NE.V(NT2)) GO TO 71
      JCODE=.FALSE.
      GO TO 68
71    CONTINUE
      GO TO 60
16    CONTINUE
      NCNT=0
      JI=6
      DO 30 J=6,NT2
      JJ=J
      IF (KON(J) .EQ. 1) GO TO 31
      IF (NCNT .GT. 4) GO TO 33
      DO 32 JIJ=JI,JJ
      KON(JIJ)=0
32    CONTINUE
33    NCNT=0
      JI=J
      GO TO 30
31    NCNT=NCNT+1
30    CONTINUE
      IF (K .NE. 2) GO TO 801
      CALL LABEL(FH)
801   CONTINUE
      DO 800 J=6,NT2
      JUL=NXV(U(J))
      JVL=NYV(V(J))
      JUR=NXV(U(J+1))
      JVR=NYV(V(J+1))
C     WRITE (6,1003) JUL,JVL,JUR,JVR
1003  FORMAT(1X,4I6)
      IF (KON(J+1) .NE. 0) CALL LINEV(JUL,JVL,JUR,JVR)
800   CONTINUE
      15  FH=FH+FHINC
100   FORMAT (45H WARNING IN SUBROUTINE CONTOR AT A HEIGHT OF ,
1F7.1,
246HNUMBER OF POINTS EXCEEDED ALLOWABLE NUMBER OF ,
3I5,/,
421HEXECUTION CONTINUING ,//)
101   FORMAT (28H ERROR IN SUBROUTINE CONTOR ,//111,

```

```

121H=NUMBER OF GRID ROWS ,/,I11,
224H=NUMBER OF GRID COLUMNS ,/,F11.3,
333H=DISTANCE BETWEEN CONTOUR LABELS ,/,I11,
429H=FREQUENCY OF CONTOUR LABELS ,/,
521H=EXECUTION TERMINATED ,// )
  RETURN
  END

```

# \$IBFTC STRK

```

  SUBROUTINE STRIKE(V1,V2,V3,FH,P1,P2,IFR)
  DIMENSION V1(1),V2(1),V3(1),P1(1),P2(1),Q(3,3)
  DO 6 I=1,3
    P1(I)=0.0
    P2(I)=0.0
    Q(I,1)=V1(I)
    Q(I,2)=V2(I)
6    Q(I,3)=V3(I)
1000 FORMAT (1X,3F10.5)
    DO 7 I=1,3
      II=I
      DO 1 J=1,3
        IF (Q(3,II)-Q(3,J)) 1,1,2
2      DO 8 L=1,3
        A=Q(L,II)
        Q(L,II)=Q(L,J)
        Q(L,J)=A
8      CONTINUE
1      CONTINUE
7      CONTINUE
      IER=0
      IF(Q(3,3).LT.FH.OR. Q(3,1).GT.FH) RETURN
      IF(Q(3,1).EQ.FH.AND.Q(3,2).EQ.FH.AND.Q(3,3).EQ.FH) RETURN
      A=(FH-Q(3,1))/(Q(3,1)-Q(3,3))
      P1(1)=(Q(1,1)-Q(1,3))*A+Q(1,1)
      P1(2)=(Q(2,1)-Q(2,3))*A+Q(2,1)
      P1(3)=FH
      IF (Q(2,1) .NE. FH) GO TO 3
      IF (Q(3,2) .NE. FH) GO TO 4
      P2(1)=Q(1,2)
      P2(2)=Q(2,2)
      P2(3)=Q(3,2)
      IER=2
      RETURN
3    IF (Q(3,2) .GT. FH) GO TO 5
      A=(FH-Q(3,2))/(Q(3,2)-Q(3,3))
      P2(1)=(Q(1,2)-Q(1,3))*A+Q(1,2)
      P2(2)=(Q(2,2)-Q(2,3))*A+Q(2,2)
      P2(3)=FH
      IER=2
      RETURN
4    IER=1
      P2(1)=P1(1)
      P2(2)=P1(2)
      P2(3)=FH

```

```

      RETURN
5     A=(FH-Q(3,1))/(Q(3,1)-Q(3,2))
      P2(1)=(Q(1,1)-Q(1,2))*A+Q(1,1)
      P2(2)=(Q(2,1)-Q(2,2))*A+Q(2,1)
      P2(3)=FH
      IER=2
      RETURN
      END

```

```

$IBFTC MARK
      SURROUTINF LABEL(H)
      COMMON /LAB /N13,NF3,NT3,Z(2560),KON(3400),N12,NF2,NT2,U(3400),
1V(3400)
      I2=5
12     I1=I2+1
      DIS=0.0
      IS=I1+1
      IF (I1+4 .GT. NT2) GO TO 99
      DO 10 I2=IS,NT2
      IF (KON(I2) .EQ. 0) GO TO 11
10     DIS=DIS+SQRT((U(I2)-U(I2-1))**2+(V(I2)-V(I2-1))**2)
11     I12=I2-1
      IF (DIS .LT. 270.0) GO TO 12
      IM=(I12+I1)/2
      IDIF=(I12-I1)/2
      IF (IDIF .LT. 2) GO TO 12
      DO 20 J=1,IDIF
      IL=IM-1
      IU=IM+J
      DIS=SQRT((U(IU)-U(IL))**2+(V(IU)-V(IL))**2)
      IF (DIS .GT. 68.0) GO TO 16
20     CONTINUE
      GO TO 12
16     IS=IL+1
      DO 19 JJ=IS,IU
19     KON(JJ)=0
      REALM=10.0E+10
      IF (U(IU)-U(IL) .NE. 0.0) REALM=(V(IU)-V(IL))/(U(IU)-U(IL))
      ANGL=ATAN(REALM)
      R=(DIS-68.0)/2.0
      S=68.0+R
      IF (U(IU) .GT. U(IL)) GO TO 30
      II=IU
      IU=IL
      IL=II
30     XP=(R*U(IU)+S*U(IL))/DIS+6.8*SIN(ANGL)
      YP=(R*V(IU)+S*V(IL))/DIS-6.8*COS(ANGL)
      DO 18 JJ=1,5
      ND=5-JJ
      IF (ARS(H) .LT. 10.0**((JJ-1))) GO TO 17
18     CONTINUE
17     CONTINUE
      IXP=XP
      IYP=YP

```

```

CALL LABLV(H,IXP,IYP,ND,1,5)
GO TO 12
99 RETURN
END

```

```

$ORIGIN          ALPHA,SYSUT2,REW
$IRF7C MOD6
SUBROUTINE BWNDR3
  DIMENSION X(12,256),Y(12,256),MCHAN(12),NN( 256),KSYM(49),JSYM(
1256)
  DIMENSION NWHICH(12)
  NAMELIST/INPUT6/NSCANS,NSTART,NSPS,NCH,NVAR,NSYM,ISUM,NRTL6,
1MODE,ITYPE,MSFC ,NSKIP,NBLK,INCX,INCY,NSTX,NSTY,NCRE
  NAMELIST/NCHUSE/NWHICH
  EQUIVALENCE (NSCAN,NSCANS)
  EQUIVALENCE (NSTRT,NSTART)
  EQUIVALENCE (NCOL,NSPS)
  EQUIVALENCE (NCHAN,NCH)
  ICARD=5
  IPRINT=6
  INTAPE=10
  IOTAPE=11
  READ(ICARD,INPUT6)
  WRITE (IPRINT,INPUT6)
  READ(ICARD,NCHUSE)
  WRITE(IPRINT,NCHUSE)
1 FORMAT(1X,7I4)
3 FORMAT(1X,12I1)
  READ(ICARD,5)(KSYM(I),I=1,NSYM)
5 FORMAT(1X,60A1)
  NFLAG=0
  AVE=ISUM
  APOP=0.0
  DXAVF=0.0
  DYAVF=0.0
  DZAVF=0.0
  NSAV=NSCAN
  IF (NSKIP .EQ. 0) GO TO 98
  DO 97 I=1,NSKIP
  CALL SKRBIN(INTAPE,1,NOP)
97 CONTINUE
98 CONTINUE
2 FORMAT(1H1)
4 FORMAT(5X,11I1)
  II=1
  KK=NSTRT-1
160 IF(II.EQ.NSCAN) GO TO 510
  II=II+1
  NFLAG2=1

```

```

      KK=KK+1
      IF(II.NE.2) GO TO 290
      DO 170 JJ=1,NCOL
      CALL GET6(X(1,JJ),NCOL,0,NCHAN,NSCANO,INTAPE,IFRR,NFLAG2,NSTRT,
170 INRTLG,MODE,NCRF,ITYPE,MSFC)
      CONTINUE
      290 CONTINUE
      NFLAG2=1
      DO 300 JJ=1,NCOL
      CALL GET6(Y(1,JJ),NCOL,0,NCHAN,NSCANO,INTAPE,IFRR,NFLAG2,NSTRT,
300 INRTLG,MODE,NCRF,ITYPE,MSFC)
      CONTINUE
      DO 380 JJ=2,NCOL
      IJ=JJ-1
      XSUM=0.0
      YSUM=0.0
      ZSUM=0.0
      DO 360 ICHAN=1,ISUM
      IICHN=NWHICH(ICHAN)
      XDIFF=Y(IICHN,JJ)-Y(IICHN,IJ)
      YDIFF=Y(IICHN,JJ)-X(IICHN,JJ)
      XSUM=XSUM+XDIFF*XDIFF
      YSUM=YSUM+YDIFF*YDIFF
      ZSUM=ZSUM+XDIFF*YDIFF
360 CONTINUE
      XSUM=XSUM/AVE
      YSUM=YSUM/AVE
      ZSUM=ZSUM/AVE
      APOP=APOP+1.0
      AA=1.0/APOP
      BB=1.0-AA
      DXAVE=BB*DXAVE+AA*YSUM
      DYAVE=BB*DYAVE+AA*XSUM
      DZAVE=BB*DZAVE+AA*ZSUM
      XSUM=SQRT(XSUM)
      IF (XSUM .LT. 53.4) GO TO 365
364 XSUM=53.0
      YSUM=53.0
      GO TO 366
365 CONTINUE
      YSUM=SQRT(YSUM)
      IF (YSUM .LT. 53.4) GO TO 366
      GO TO 364
366 CONTINUE
      CALL JNTPB(YSUM,XSUM,NFLAG,0,0,KSYP(3),NPOP,
2DXAVE,DYAVE,
3DZAVE,
1JJ,NSCAN,II,NCOL,JSYM,X,NSTRT,NN,INCX)
      NSCAN=NSAV
380 CONTINUE
      DO 500 JJ=1,NCOL
      DO 490 ICHAN=1,ISUM
      IICHN=NWHICH(ICHAN)
      X(IICHN,JJ)=Y(IICHN,JJ)
490 CONTINUE

```

```

500 CONTINUE
    GO TO 160
510 CONTINUE
    NFLAG=1
    CALL JNTPB(YSUM,XSUM,NFLAG,0,0,KSVM(3),NPOP,
2DXAVE,DYAVE,
3DZAVE,
1JJ,NSCAN,II,NCOL,JSYM,X,NSTRT,NN,INCX)
    REWIND IOTAPF
    REWIND INTAPE
C    CALL CLEAN
    RETURN
    END

```

```

$IRFTC PLOTT6
    SUBROUTINE LABFL6(NSTART,NSTOP,INCREF )
    DIMENSION IOUT(120)
    NDIF=(NSTOP-NSTART+1)/INCREF
    II=0
    DO 1 I=NSTART,NSTOP,INCREF
    II=II+1
    IOUT(II)=I/1000
1    CONTINUE
    WRITE (6,10) (IOUT(I),I=1,NDIF)
    II=0
    DO 2 I=NSTART,NSTOP,INCREF
    II=II+1
    IOUT(II)=I/100-I/1000*10
2    CONTINUE
    WRITE (6,10) (IOUT(I),I=1,NDIF)
    II=0
    DO 3 I=NSTART,NSTOP,INCREF
    II=II+1
    IOUT(II)=I/10-I/100*10
3    CONTINUE
    WRITE (6,10) (IOUT(I),I=1,NDIF)
    II=0
    DO 4 I=NSTART,NSTOP,INCREF
    II=II+1
    IOUT(II)=I-I/10*10
    IF (IOUT(II) .LE. 0 ) IOUT(II)=0
4    CONTINUE
    WRITE (6,10) (IOUT(I),I=1,NDIF)
10   FORMAT (11X,120I1)
    RETURN
    END

```

```

$IRFTC GETDA6
    SUBROUTINE GET6(DATA,NSPS,NSKIP,NCPW,NSCANO,IRW,IERR,NFLAG2,
1NSTART,NPTLG,MODE,NCRE,ITYPE,MSFC )
    DIMENSION DATA(1),NDAT( 890)
    DATA NFLAG/0/
    IF (NFLAG .NE. 0 ) GO TO 12

```



```

NSCANO=0
NTEMP=(NCRE-1)*NCPW
NL=36-NBTLG
NBLNG=36/NBTLG
NFLAG=1
NSTMP=(NSPS+NSTART-1)*NCPW+MSFC*19
NSCANS=NSTMP
NTMP=NSTMP/NBLNG
NSTMP=NSTMP/NBLNG*NBLNG
IF (NSTMP .LT. NSCANS) NTMP=NTMP+1
NSCANS=NTMP
IF (NSKIP .EQ. 0) GO TO 402
DO 401 I=1,NSKIP
NSCANO=NSCANO+1
CALL SKRBIN (IRW,1,RD )
401 CONTINUE
402 CONTINUE
12 CONTINUE
IF (NFLAG2 .EQ. 0) GO TO 10
13 CONTINUE
M=(NSTART-1)*NCPW+MSFC*19
IF (MODE .EQ. 1) GO TO 50
CALL REDTPR (IRW,MODE,IERR,NW,NSCANS,NDAT)
GO TO 51
50 CALL REDTPC (IRW,MODE,IFERR,NW,NSCANS,NDAT)
51 CONTINUE
1000 FORMAT (1X,I6)
NNW=NW*6
NFLAG2=0
NSCANO=NSCANO+1
10 CONTINUE
DO 14 NN=1,NCPW
IR=M+NBLNG
ID=IR/NBLNG
IF=IR-NBLNG*ID
IBIT=NBTLG*IF
M=M+1
IF (ITYPE .EQ. 1) GO TO 15
NDATA=0
CALL FLD(NDATA,NL,NBTLG,IBIT,NDAT(ID))
DATA(NN)=NDATA
GO TO 14
15 CONTINUE
DATAN=0.0
CALL FLD(DATAN,NL,NBTLG,IBIT,NDAT(ID))
DATA(NN)=DATAN
14 CONTINUE
M=M+NTEMP
RETURN
END

```

```

$IBFTC JOINT
SUBROUTINE JNTPB(DATAH,DATAV,NFLAG,MIX,MIY,ALPNUM,NPOP,
2DXAVF,DYAVF,

```

```

3DZAVE,
1JJ,NSCAN,ISCAN,NCOL,ISYM,NX,NSTRT,NN,INCXY)
  DIMENSION INCXY(1)
  DIMENSION NP(54,54)
  DIMENSION DATA(12)
  DIMENSION IBIN(255 )
  DIMENSION ISYM(1),IQUIT(100)
  DIMENSION NX(1),NN(1)
  DIMENSION ALPNUM( 1),ALPHA(120),CORDX(3)
  DOUBLE PRECISION A(2,2),EIGEN(2,2)
  INTEGER ALPNUM,ALPHA,BLANK
  DATA ASTRIK/1H*/
  DATA XMARK/1HX/
  DATA BLANK/6H      /
  DATA NFLAG4/0/
1060 FORMAT(48X,25HDATA SWITCH HAS OCCURRED      )
1061 FORMAT(49X,30HJOINT PROBABILITY DISTRIBUTION  )
1062 FORMAT(1H1)
1063 FORMAT(44X,11H X-AXIS IS ,I6,6X,11H Y-AXIS IS ,2I6)
1066 FORMAT (30X,6HDXAVE=,F15.7,6HDYAVE=,F15.7,6HDZAVE=,F15.7      )
1040 FORMAT(1H ,67H MAXIMUM PROBABILITY OF UNCOMMONALITY EXCEEDED- CONT
  INUE EXECUTION      ,2I6)
1064 FORMAT(1X,26HSYMBOL      N/SYMBOL      )
1065 FORMAT(11X,121(1H*),/,11X,1H*,55X,5HPART ,I1,4H OF ,I1,53X,1H*,/
  1,11X,121(1H*))
  IF (NFLAG4 .GT. 0) GO TO 80
  NFLAG3=0
1000 FORMAT(1X,47A1)
  NFLAG=0
  NI=2
  IRW=1
  NFLAGFN=0
  IRT=11
  DO 1 I=1,54
  DO 1 J=1,54
  NP(I,J) =0
1  CONTINUE
  REWIND IRT
  REWIND IRW
  NFLAG4=1
80  CONTINUE
  IF (NFLAG.GT. 0) GO TO 13
  NC=DATAV+1.5
  NR=DATAH+1.5
  IF (NC .LT. 1) NC=1
  IF (NR .LT. 1) NR=1
  NP(NR,NC)=NP(NR,NC)+1
  I=54*(NC-1)+NR
  IRIN(JJ)=I
  IF (JJ .LT. NCOL) GO TO 15
  IRIN(1)=IRIN(2)
  WRITE(IRW)(IRIN(II),II=1,NCOL)
15  CONTINUE
  RETURN
13  CONTINUE

```

```

17  CONTINUE
    REWIND IRW
    IOPT=1
    IN=2
    IM=2
    RHO=1.0/(10.0**5)
    A(1,1)=DXAVE
    A(2,2)=DYAVE
    A(1,2)=DZAVE
    A(2,1)=DZAVF
    CALL DJCOBI(A,IM,IN,IOPT,RHO,ERR,FIGEN)
C   WRITE(6,1067) A(1,1),A(1,2),FIGEN(1,1),EIGEN(1,2)
C   WRITE(6,1067) A(2,1),A(2,2),EIGEN(2,1),EIGEN(2,2)
1067 FORMAT(1X,2E15.7,10X,2F15.7)
    DXAVE=1.0/A(1,1)
    DYAVE=1.0/A(2,2)
    A(1,1)=EIGEN(1,1)*DXAVE
    A(1,2)=EIGEN(2,1)*DXAVE
    A(2,1)=EIGEN(1,2)*DYAVE
    A(2,2)=EIGEN(2,2)*DYAVE
    DXAVE=EIGEN(1,1)*A(1,1)+EIGEN(1,2)*A(2,1)
    DYAVE=EIGEN(2,1)*A(1,2)+EIGEN(2,2)*A(2,2)
    DZAVE=EIGEN(1,1)*A(1,2)+EIGEN(1,2)*A(2,2)+EIGEN(2,1)*A(1,1)
    1+EIGEN(2,2)*A(2,1)
    WRITE(6,1066) DXAVE,DYAVE,DZAVE
    I=0
    DO 130 NC=1,54
    DO 130 NR=1,54
    I=I+1
    IF (NP(NR,NC) .EQ. 0) GO TO 130
    XXX=NR*NR
    YYY=NC*NC
    ZZZ=NR*NC
    SUM=DXAVE*XXX+DYAVE*YYY
    1+DZAVE*ZZZ
    IF(SUM.GF.1.0)GO TO 115
    NX(I)=0
    GO TO 130
115  NX(I)=-1
130  CONTINUE
    WRITE (6,1062)
    WRITE(6,1061)
    WRITE(6,1066) DXAVE,DYAVE,DZAVE
    WRITE(6,1064)
C   CALCULATE TABLE
    MAXKNT=0
    DO 22 NC=1,53
    DO 22 NR=1,53
    IF (NP(NR,NC) .GT. MAXKNT) MAXKNT=NP(NR,NC)
22  CONTINUE
    IF (MAXKNT .LT. 46 ) MAXKNT=46
    NFACT=MAXKNT/45
    XXX=FLOAT(MAXKNT)/46.0
    NFAC=0
    IF (NFACT .LT. 1) NFACT=1

```

```

        WRITE(6,1050) BLANK,NFAC
        NFAC=NFAC+NFACT
        DO 23 I=1,46
        WRITE(6,1050) ALPNUM(I),NFAC
1050  FORMAT (3X,A6,6X,I6)
        NFAC=NFAC+NFACT
23    CONTINUE
        WRITE(6,1062)
C      PRINT DISTRIBUTION ON PAGE
        CORDX(1)=0.0
        CORDX(2)=CORDX(1)+60.0
        CORDX(3)=CORDX(1)+110.0
1021  FORMAT (1H1)
        DO 65 IEND=1,54
        NC=55-IEND
        DO 66 I=1,54
        ALPHA(I)=BLANK
66    CONTINUE
        IF (NFLG .EQ. 1) GO TO 69
        DO 68 I=1,54
        IBIN(I)=0
68    CONTINUE
69    CONTINUE
        DO 64 NR=1,54
        XX=FLOAT(NP(NR,NC))
        IF (NFLG .EQ. 1) GO TO 91
        IBIN(NR)=NP(NR,NC)
91    CONTINUE
        ICAR=XX+(1.001-1.0/XXX)
        IF (ICAR .GT. 46 ) ICAR=46
        ALPHA(NR)=ALPNUM(ICAR)
64    CONTINUE
        CORDY=FLOAT(NC)
        YMARG=XMARK
        IF (NC .NE. 54-IEND/10*10) YMARG=ASTRIK
        WRITE(6,1008) CORDY,YMARG,(ALPHA(I),I=1,54)
1008  FORMAT(1X,F8.1,2X,A1,120A1)
65    CONTINUE
        WRITE(6,1010)
        WRITE(6,1011) CORDX(1),CORDX(2),CORDX(3)
1011  FORMAT (6X,F10.4,50X,F10.4,40X,F10.4)
        NFLG=1
        WRITE(6,1062)
        NSUB=1
        LWFR=1
        LOW=NSTRT
705   CONTINUE
        NHI=LOW+120-1
        NUPPER=LWFR+120-1
        IF (NUPPER .GT. NCOL) NUPPER=NCOL
        WRITE(6,1062)
        CALL LABEL6(LOW,NHI,1)
        DO 131 II=NI,NSCAN
        READ(IRW) (IBIN(JJ),JJ=1,NCOL)
        DO 135 JJ=1,NCOL

```

```

        ICHECK=IRIN(JJ)
        JCHECK=NX(ICHECK)
        IF (JCHECK .NE. 0) GO TO 117
        ISYM(JJ)=ALPNUM(NSUB-1)
        NN(JJ)=0
        GO TO 135
117     ISYM(JJ)=ALPNUM(NSUB)
        NN(JJ)=-1
135     CONTINUE
        IF (NFLGFN .NE. 0) GO TO 136
        WRITE(IRT) (NN(JJ),JJ=1,NCOL)
        CALL PLTRF6(ISYM,NCOL,NBLK,INCXY(1),INCXY(2),INCXY(3),
1INCXY(4),NCRE)
136     CONTINUE
        WRITE(6,1036) II, (ISYM(JJ),JJ=LWER,NUPPER)
1036    FORMAT(5X,I6,120A1)
1035    FORMAT(1X,I6)
131     CONTINUE
        NFLGFN=1
        REWIND IRW
        LWER=NUPPER+1
        LOW=NHI+1
        IF (NUPPER .LT. NCOL) GO TO 705
995     CONTINUE
1010    FORMAT (11X,12(10HX*****))
        NFLGFN=0
        RETURN
        END

```

```

$IBFTC PLLT6
SUBROUTINE PLTBF6(ISYM,NN,NSQR,INCX,INCY,NSTX,NSTY,NCRE)
DIMENSION ISYM(1),NBUFER(50)
DATA NFLAG/0/
DATA NFLAG1/0/
IF (NFLAG .NE. 0) GO TO 10
CALL CAMRAV(35)
CALL BUTTV(1)
10     CONTINUE
        IF (NFLAG1 .NE. 0) GO TO 20
        CALL FRAMEV(0)
        NCOUNT=0
        INCRX=NSTX
        INCRY=NSTY
        NFLAG1=1
        IF (NFLAG .EQ. 0) GO TO 11
        CALL APRNTV (INCX,INCY,NN,NBUFER,INCRX,INCRY)
        INCRY=INCRY+INCX
        INCRX=INCRX+IARS(INCY)
        NCOUNT=NCOUNT+1
11     NFLAG=1
20     CONTINUE
        NCOUNT=NCOUNT+1
        DO 1 I=1,50
        NBUFER(I)=0

```

```

1    CONTINUE
      IA=0
      DO 2 I=1,NN
        IB=IA+6
        IC=IB/6
        ID=IB-IC*6
        IE=ID*6
        IA=IA+1
        CALL FLD(NBUFFER(IC),IF,6, 0,ISYM(I))
2    CONTINUE
      CALL APRNTV(INCX,INCY,NN,NBUFFER,INCRX,INCRY)
      INCRY=INCRY+INCX
      INCRX=INCRX+IABS(INCY)
      IF (INCRX .GE. 1023) NFLAG1=0
      RETURN
      END

```

```

$ORIGIN      ALPHA,SYSUT2,REW
$IBFTC MOD7
      SUBROUTINE CLASFY
        COMMON /LAB1/XBAR(42,12),SIGMA(42,12),ROT(42,12,12)
        COMMON /LAB2/X(12),ALPHA(49),NSPS,NSCANS,NCHAN,LT9,LT10,LT11,LT12,
1LT13,LT1,IXXX,IYYY,
1INSTART,NSTOP,
1NBTLG,MODE,ITYPE,MSFC,I4,NCRE,
1NSKIP,INCX,INCY,NSTX,NSTY
        NAMELIST/INPUT7/NPASS,NCLUST
        NAMELIST/INPUTA/NSPS,NSCANS,NCH, LT1,LT9,LT10,LT11,LT12,LT13,
1INSTART,NSTOP,NBTLG,MODE,ITYPE,MSFC,I4,NCRE,NSKIP,INCX,INCY,NSTX,
2NSTY,IXXX,IYYY
        EQUIVALENCE (NCH,NCHAN)
        RFAD(5,INPUT7)
        RFAD(5,INPUTA)
        WRITE(6,INPUTA)
        READ(5,1006) (ALPHA(I),I=1,48)
1006 FORMAT(1X,60A1)
        KOUNT=NCLUST
        NSCANS=NSCANS-1
        INITCL=NCLUST+1
        DO 1 I=1,NPASS
          CALL TRUCK(NCLUST,NPASS )
          CALL SEQMRG (NCLUST,KOUNT,INITCL )
          CALL CLASS (KOUNT , I, NPASS )
          NCLUST=KOUNT
          INITCL=KOUNT+1
1    CONTINUE
      RETURN
      END

```

```

$IBFTC GETDA7
      SUBROUTINE GET7(DATA,NSPS,NSKIP,NCPW,NSCANO,IRW,IERR,NFLAG2,
1  INSTART,NBTLG,MODE,NCRE,ITYPE,MSFC )
      DIMENSION DATA(1),NDAT( 890)
      DATA NFLAG/0/
      IF (NFLAG .NE. 0 ) GO TO 12
      NSCANO=0
      NTEMP=NCPW*(NCRE-1)
      NL=36-NBTLG
      NBLNG=36/NBTLG
      NFLAG=1
      NSTMP=(NSPS+INSTART-1)*NCPW+MSFC*19
      NSCANS=NSTMP
      NTMP=NSTMP/NBLNG
      NSTMP=NSTMP/NBLNG*NBLNG
      IF (NSTMP .LT. NSCANS) NTMP=NTMP+1
      NSCANS=NTMP
      IF (NSKIP .EQ. 0) GO TO 402
      DO 401 I=1,NSKIP
      NSCANO=NSCANO+1
      CALL SKRRIN (IRW,1,RD )
401  CONTINUE
402  CONTINUE
12   CONTINUE
      IF (NFLAG2 .EQ. 0) GO TO 10
13   CONTINUE
      M=(NSTART-1)*NCPW+MSFC*19
      IF (MODE .EQ. 1) GO TO 50
      CALL REDTPR (IRW,MODE,IERR,NW,NSCANS,NDAT)
      GO TO 51
50   CALL REDTPC (IRW,MODE,IERR,NW,NSCANS,NDAT)
51   CONTINUE
1000 FORMAT (1X,I6)
      NNW=NW*6
      NFLAG2=0
      NSCANO=NSCANO+1
10   CONTINUE
      DO 14 NN=1,NCPW
      IB=M+NBLNG
      ID=IB/NBLNG
      IF=IB-NBLNG*ID
      IBIT=NBTLG*IF
      M=M+1
      IF (ITYPE .EQ. 1) GO TO 15
      NDATA=0
      CALL FLD(NDATA,NL,NBTLG,IBIT,NDAT(ID))
      DATA(NN)=NDATA
      GO TO 14
15   CONTINUE
      DATAN=0.0
      CALL FLD(DATAN,NL,NBTLG,IBIT,NDAT(ID))
      DATA(NN)=DATAN
14   CONTINUE
      M=M+NTEMP

```

```

RETURN
END

```

```

$IBFTF PLOTT7
  SUBROUTINE LABEL7 (NSTART,NSTOP,INCRF      )
    DIMENSION IOUT(120)
    NDIF=(NSTOP-NSTART+1)/INCRF
    II=0
    DO 1 I=NSTART,NSTOP,INCRF
      II=II+1
      IOUT(II)=I/1000
1    CONTINUE
      WRITE (6,10) (IOUT(I),I=1,NDIF)
      II=0
      DO 2 I=NSTART,NSTOP,INCRF
        II=II+1
        IOUT(II)=I/100-I/1000*10
2      CONTINUE
        WRITE (6,10) (IOUT(I),I=1,NDIF)
        II=0
        DO 3 I=NSTART,NSTOP,INCRF
          II=II+1
          IOUT(II)=I/10-I/100*10
3        CONTINUE
          WRITE (6,10) (IOUT(I),I=1,NDIF)
          II=0
          DO 4 I=NSTART,NSTOP,INCRF
            II=II+1
            IOUT(II)=I-I/10*10
            IF (IOUT(II) .LE. 0 ) IOUT(II)=0
4          CONTINUE
            WRITE (6,10) (IOUT(I),I=1,NDIF)
10         FORMAT (11X,120I1)
          RETURN
        END

```

```

$IBFTC PLLTT7
  SUBROUTINE PLTRF7(ISYM,NN,NSQR,INCX,INCY,NSTX,NSTY,NCRE,
1  NFLAG,NFLAG1)
    DIMENSION ISYM(1),NBUFER(50)
    DATA NFLG/0/
    IF (NFLG .NE. 0) GO TO 10
    NFLG=1
    CALL CAMRAV(35)
    CALL BUTTV(1)
    NSQR=1024/ABS(INCY+INCX)
10   CONTINUE
    IF (NFLAG1 .NE. 0) GO TO 20
    CALL FRAMEV(0)
    NCOUNT=0
    INCRX=NSTX
    INCRY=NSTY
    NFLAG1=1

```



```

      IF (NFLAG .EQ. 0) GO TO 11
      CALL APRNTV (INCX, INCY, NN, NBUFER, INCRX, INCY)
      INCY=INCRX+INCX
      INCRX=INCRX+IABS(INCY)
      NCOUNT=NCOUNT+1
11     NFLAG=1
20     CONTINUE
      NCOUNT=NCOUNT+1
      DO 1 I=1,50
      NBUFER(I)=0
1     CONTINUE
      IA=0
      DO 2 I=1,NN,NCRE
      IB=IA+6
      IC=IB/6
      ID=IB-IC*6
      IE=ID*6
      IA=IA+1
      CALL FLD(NBUFER(IC),IE,6, 0, ISYM(I))
2     CONTINUE
      CALL APRNTV (INCX, INCY, NN, NBUFER, INCRX, INCY)
      INCY=INCRX+INCX
      INCRX=INCRX+IABS(INCY)
      IF (INCRX .GE. 1024) NFLAG1=0
      RETURN
      END

```

\$ORIGIN BRAVO, SYSUT2, REW

\$IRFTC MOD7A

```

      SUBROUTINE TRUCK(NCCT,NPASS
      DIMENSION NNACC(12,256),MTAB(11),IPRT(256),IPLOT(256)
      DIMENSION NTBL(400)
      COMMON /LAB1/XBAR(42,12),SIGMA(42,12),ROT(42,12,12)
      COMMON /LAB2/X(12),NSYM(49),NSPS,NSCANS,NCHAN,LT9,LT10,LT11,LT12,
1LT13,LT1,IXXX,IYYY,
1NSTART,NSTOP,
1NRTLG,MODE,ITYPE,MSFC,I4,NCRE,
1NSKIP,INCX,INCY,NSTX,NSTY
      NFLGXX=0
      NFLAGX=0
      REWIND LT11
      REWIND LT1
      NFLAG1=0
      MFIN=0
      IXIY=IXXX*IYYY
      DO 10 I=1,IYYY
      MTAB(I)=I
10     CONTINUE
      DO 50 I=1,400
      NTBL(I)=I
50     CONTINUE
      DO 11 I=1,IYYY
      READ(LT11) (NNACC(I,JJ),JJ=1,NSPS)
      MFIN=MFIN+1

```

```

11  CONTINUE
    NUP=NSPS-IXXX+1
    NCNT=NCCNT+1
    NFLAG=0
200  CONTINUE
    III=MTAB(1)
    DO 110 JJ=1,NSPS
    IF (JJ .GT. NUP) GO TO 102
    IJ=JJ
    JI=JJ+IXXX-1
    NZERO=0
    IKNT=0
    ISUM=0
    JIJ=MTAB(1)
    NTEMP= NCCNT+1
    DO 101 I=IJ,JI
    DO 100 JIJ=1,IYYY
    IJJ=MTAB(JIJ)
    IF (NNACC(IJJ,I) .LE. NCCNT .AND. NNACC(IJJ,I) .NE. 0) GO TO 102
    IF (NNACC(IJJ,I)) 102,107,106
106  IF (NNACC(IJJ,I) .GT. NTEMP) NTEMP=NNACC(IJJ,I)
    GO TO 100
107  NZERO=NZERO+1
100  CONTINUE
101  CONTINUE
    IF (NZERO .NE. IXIY) GO TO 105
    DO 103 I=IJ,JI
    DO 104 JIJ=1,IYYY
    NNACC(JIJ,I)=NCNT
104  CONTINUE
103  CONTINUE
    NCNT=NCNT+1
    IF (NCNT .GT. 400) GO TO 999
    GO TO 110
105  CONTINUE
    DO 108 I=IJ,JI
    DO 108 JIJ=1,IYYY
    IF (NNACC(JIJ,I) .EQ. 0) NNACC(JIJ,I)=NTEMP
108  CONTINUE
    GO TO 110
102  CONTINUE
110  CONTINUE
    DO 111 JJ=1,NSPS
    IF (JJ .EQ. NSPS ) GO TO 111
    IF (NNACC(III,JJ) .LE. NCCNT) GO TO 111
    IF (NNACC(III,JJ+1) .LE. NCCNT) GO TO 111
    IF (NNACC(III,JJ) .LE. 0) GO TO 111
    IF (NNACC(III,JJ+1) .LE. 0) GO TO 111
    IF (NNACC(III,JJ) .EQ. NNACC(III,JJ+1)) GO TO 111
    IJ=NNACC(III,JJ)
    JI=NNACC(III,JJ+1)
    IF (JI .GT. 400 .OR. IJ .GT. 400) GO TO 111
    IF (NTBL(JI) .GT. NTBL(IJ)) GO TO 125
    NTBL(IJ)=NTBL(JI)
    GO TO 111

```

```

125  CONTINUE
    NTBL(JI)=NTBL(IJ)
111  CONTINUE
1007 FORMAT (1X,I6)
    WRITE(LT1) (NNACC(III,JJ),JJ=1,NSPS)
    IF (MFIN .GE. NSCANS) GO TO 999
    IYI=MTAB(1)
    READ(LT11) (NNACC(IYI,JJ),JJ=1,NSPS)
    MFIN=MFIN+1
    NTFMP=MTAB(1)
    IYY=IYYY-1
    DO 121 I=1,IYY
    MTAB(I)=MTAB(I+1)
121  CONTINUE
    MTAB(IYYY)=NTEMP
    GO TO 200
999  CONTINUE
    DO 122 I=2,IYYY
    III=MTAB(I)
    DO 112 JJ=1,NSPS
    IF (JJ .EQ. NSPS ) GO TO 112
    IF (NNACC(III,JJ) .LE. NCCNT) GO TO 112
    IF (NNACC(III,JJ+1) .LE. NCCNT) GO TO 112
    IF (NNACC(III,JJ) .LE. 0) GO TO 112
    IF (NNACC(III,JJ+1) .LE. 0) GO TO 112
    IF (NNACC(III,JJ) .EQ. NNACC(III,JJ+1)) GO TO 112
    IJ=NNACC(III,JJ)
    JI=NNACC(III,JJ+1)
    IF (JI .GT. 400 .OR. IJ .GT. 400) GO TO 112
    IF (NTRL(JI) .GT. NTRL(IJ)) GO TO 126
    NTRL(IJ)=NTRL(JI)
    GO TO 112
126  CONTINUE
    NTRL(JI)=NTRL(IJ)
112  CONTINUE
    WRITE(LT1) (NNACC(III,JJ),JJ=1,NSPS)
122  CONTINUE
    END FILE LT1
    REWIND LT1
    REWIND LT11
    REWIND LT12
    WRITE(6,1007) (NTBL(I),I=1,400)
    DO 113 I=1,400
    IF (NTBL(I) .EQ. 1) GO TO 113
    JI=I+1
    IF (NTBL(JI) .NE. 1) GO TO 114
    NTRL(JI)=NTRL(I)
114  CONTINUE
113  CONTINUE
    II=1
    NTEMP=II
    DO 116 I=2,400
    IF (NTBL(I)-NTRL(I-1)) 117,118,119
119  IF (NTBL(I) .NE. 1) GO TO 117
    NTRL(I-1)=NTEMP

```

```

      II=II+1
      NTEMP=II
      GO TO 116
118  NTBL(I-1)=NTEMP
      GO TO 116
117  N=NTBL(I)
      NTBL(I-1)=NTEMP
      NTEMP=NTBL(N)
116  CONTINUE
      NTBL(400)=NTEMP
      WRITE(6,1007) (NTBL(I),I=1,400)
      LWER=1
      LOW=NSTART
705  CONTINUE
      NUPPER=LWER+120-1
      NHI=LOW+120-1
      IF (NUPPER .GT. NSPS ) NUPPER=NSPS
      IDIF=NUPPER-LWER+1
      WRITE(6,1005)
1005 FORMAT(1H1)
      CALL LABEL7(LOW,NHI,1)
      DO 710 II=1,NSCANS
      READ(LT1) (NNACC(1,JJ),JJ=1,NSPS)
      DO 115 JJ=1,NSPS
      IB=NNACC(1,JJ)
      IF (IB .LE. 0) GO TO 115
      NNACC(1,JJ)=NTBL(IB)
115  CONTINUE
      IF (NFLGXX .GT. 0) GO TO 127
      WRITE(LT12) (NNACC(1,JJ),JJ=1,NSPS)
127  CONTINUE
      JI=0
      DO 711 JJ=LWER,NUPPER
      JI=JI+1
      N=NNACC(1,JJ)-(NNACC(1,JJ)-1)/45*45+2
      IPRT(JJ)=NSYM(N)
      IPLOT(JI)=NSYM(N)
711  CONTINUE
      WRITE(6,1003) II,(IPRT(JJ),JJ=LWER,NUPPER)
      CALL PLTRF7(IPLOT,IDIF,NBLK,INCX,INCY,NSTX,NSTY,
1003 INCRE,NFLAGX,NFLAG1)
1003 FORMAT(4X,I6,1H*,120A1)
710  CONTINUE
      REWIND LT1
      NFLAGX=0
      NFLGXX=1
      NFLAG1=0
      LWER=NUPPER+1
      LOW=NHI+1
      IF (NUPPER .LT. NSPS ) GO TO 705
570  CONTINUE
      NCCNT=NCNT-1
      END FILE LT12
      REWIND LT12
      REWIND LT1

```

```

IXXX=IXXX-4
IYYY=IYYY-4
LT11=13
RETURN
END

```

```

$ORIGIN      BRAVO,SYSUT2,REW
$IBFTC MOD7B
  SUBROUTINE SEQMRG(NCLUST,KOUNT,INITCL  )
  COMMON /LAB1/XBAR(42,12),SIGMA(42,12),ROT(42,12,12)
  COMMON /LAB2/X(12),ALPHA(49),NSPS,NSCANS,NCHAN,LT9,LT10,LT11,LT12,
1LT13,LT1,IXXX,IYYY,
1NSTART,NSTOP,
1NBTLG,MODE,ITYPE,MSFC,I4,NCRE,
1NSKIP,INCX,INCY,NSTX,NSTY
  DOUBLE PRECISION A(12,12),EIGEN(12,12)
  DIMENSION MERGE(150),MPOP(150),NEXEC(20),C(42,78),B(12,12)
  DIMENSION COM(24)
  EQUIVALENCE(COM(1),NSPS)
1000 FORMAT(1X,I6,12F10.3)
1001 FORMAT (1X,4HXBAR  )
1002 FORMAT(1X,16H DID NOT CONVERG  )
1003 FORMAT(1X,7HICLUST= ,I6,14HMERGE(ICLUST)= ,I6)
1004 FORMAT (1X,5HRHO= ,E15.7,5HERR= ,E15.7)
1005 FORMAT (1X,12F10.4)
1006 FORMAT(1X,12I6)
1007 FORMAT (1X,23HMERGING WILL TAKE PLACE  )
1008 FORMAT(1H )
1009 FORMAT (13H COV. MATRIX  )
1010 FORMAT (12H NORM EIGEN  )
1011 FORMAT (18H P.A. COV. MATRIX  )
1012 FORMAT(1H ,6HASUM= ,E15.7,7HCLUSTER,I4)
1013 FORMAT(1X,28HXBAR(I,J),J=1,12),I=1,KOUNT  )
1014 FORMAT (1X,29HSIGMA(I,J),J=1,12),I=1,KOUNT  )
1015 FORMAT(1X,55HROT(I,ICHAN,JCHAN),JCHAN=1,12),ICHAN=1,12),I=1,KOUNT
1)  )
1016 FORMAT (1X,I6,(12F10.3))
1017 FORMAT(1H1)
  NFLG=0
  CZECH=FLOAT(NCHAN)-2.0
  IF (CZECH .LE. 0.0) CZECH=1.0
  REWIND LT10
  REWIND LT12
  RHO=1.0/(10.0**5)
  IF (NSKIP .EQ. 0) GO TO 6
  DO 7 I=1,NSKIP
  CALL SKRRIN(LT10,1,NOP)
7  CONTINUE
6  CONTINUE

```

```

DO 5 ICLUST=1,NCLUST
MERGF(ICLUST)=ICLUST
5 CONTINUE
IM=NCHAN
WRITE(6,1017)
IN=IM
IOPT=1
DO 10 ICLUST=INITCL,NCLUST
IF (NFLG .GT. 0) GO TO 11
IF (KOUNT .GE. 42 ) GO TO 11
KOUNT=KOUNT+1
IFLAG=KOUNT
CALL FETCOR(IFLAG, C, MPOP,NFLG,INITCL )
WRITE(6,1001)
WRITE(6,1000) IFLAG,(XBAR(IFLAG,I),I=1,12)
MI=1
MJ=12
MK=12
DO 500 MM=1,12
WRITE(6,1000) IFLAG,(C(IFLAG,MR),MR=MI,MJ)
MI=MJ+1
MJ=MJ+MK-MM
500 CONTINUE
CALL AMTRX (IFLAG,XBAR,C,A,NCHAN)
WRITE(6,1008)
WRITE(6,1009)
WRITE(6,1005) ((A(MI,MJ),MJ=1,12),MI=1,12)
CALL DJCORI (A,IM,IN,IOPT,RHO,ERR,EIGEN)
WRITE(6,1004) RHO,FRR
WRITE(6,1005) ((A(MI,MJ),MJ=1,12),MI=1,12)
WRITE(6,1008)
WRITE(6,1005) ((EIGEN(MI,MJ),MJ=1,12),MI=1,12)
IF (ERR .EQ. 0.0) GO TO 15
MERGE(ICLUST)=0
KOUNT=KOUNT-1
WRITE(6,1002)
GO TO 10
15 CONTINUE
CALL ROTA (IFLAG,ROT,EIGEN,NCHAN,A,SIGMA)
MERGF(ICLUST)=KOUNT
WRITE(6,1003) ICLUST,MERGE(ICLUST)
MPOP(KOUNT)=MPOP(ICLUST)
IF (KOUNT .EQ. 1) GO TO 10
MCLUST=KOUNT-1
DO 20 ICHECK=1,20
NFXEC(ICHECK)=0
20 CONTINUE
MCHECK=1
DO 25 JCLUST=1,NCLUST
IF(MERGE(JCLUST).LT.MCHECK)GO TO 25
MCHECK=MCHECK+1
IF (MERGF(JCLUST) .EQ. KOUNT) GO TO 26
JFLAG=MERGE(JCLUST)
DO 30 ICHAN=1,NCHAN
X(ICHAN)=XBAR(JFLAG ,ICHAN)-XBAR(KOUNT,ICHAN)

```

```

30  CONTINUE
    IFLAG=KOUNT
    CALL KCHFCK(IFLAG,      ROT,X,SIGMA,ASUM,NCHAN)
    WRITE(6,1008)
    WRITE(6,1012)ASUM,JFLAG
    IF (ASUM .GT. CZECH) GO TO 25
    IFLAG=JFLAG
    CALL KCHECK(IFLAG,      ROT,X,SIGMA,ASUM,NCHAN)
    WRITE(6,1008)
    WRITE(6,1012)ASUM,JFLAG
    IF (ASUM .GT. CZECH) GO TO 25
    NEXEC(1)=NEXEC(1)+1
    NSUB=NEXEC(1)+1
    NEXEC(NSUB)=JFLAG
25  CONTINUE
26  IF (NEXEC(1) .EQ. 0) GO TO 10
    DO 501 KK=1,NSUB
    WRITE(6,1006) KK,NEXEC(KK)
501  CONTINUE
    MSUB=NEXEC(1)+1
    TOTAL=MPOP(KOUNT)
    DO 31 IRUN=2,MSUB
    NSUB=NEXEC(IRUN)
    SUM=MPOP(NSUB)
    TOTAL=TOTAL+SUM
31  CONTINUE
    INUM=0
    DEN=MPOP(KOUNT)
    DO 35 ICHAN=1,NCHAN
    X(ICHAN)=XBAR(KOUNT,ICHAN)*DEN/TOTAL
    DO 40 JCHAN=ICHAN,NCHAN
    INUM=INUM+1
    B(ICHAN,JCHAN)=C(KOUNT,INUM)*DEN/TOTAL
40  CONTINUE
35  CONTINUE
    DO 45 IRUN=2,MSUB
    NSUB=NEXEC(IRUN)
    INUM=0
    DEN=MPOP(NSUB)
    DO 50 ICHAN=1,NCHAN
    X(ICHAN)=X(ICHAN)+XBAR(NSUB,ICHAN)*DEN/TOTAL
    DO 55 JCHAN=ICHAN,NCHAN
    INUM=INUM+1
    B(ICHAN,JCHAN)=B(ICHAN,JCHAN)+C(NSUB,INUM)*DEN/TOTAL
55  CONTINUE
50  CONTINUE
45  CONTINUE
    DO 60 ICHAN=1,NCHAN
    DO 65 JCHAN=ICHAN,NCHAN
    A(ICHAN,JCHAN)=B(ICHAN,JCHAN)-X(ICHAN)*X(JCHAN)
    A(JCHAN,ICHAN)=A(ICHAN,JCHAN)
65  CONTINUE
60  CONTINUE
    WRITE(6,1009)
    WRITE(6,1005) ((A(MI,MJ),MJ=1,12),MI=1,12)

```

```

CALL DJCOBI(A,IM,IN,IOPT,RHO,ERR,EIGEN)
WRITE(6,1004) RHO,ERR
WRITE(6,1005) ((A(MI,MJ),MJ=1,12),MI=1,12)
WRITE(6,1008)
WRITE(6,1005) ((EIGEN(MI,MJ),MJ=1,12),MI=1,12)
IF (ERR .NE. 0.0) GO TO 10
WRITE(6,1007)
IFLAG=NEXEC(2)
MPOP(IFLAG)=TOTAL
INUM=0
DO 70 ICHAN=1,NCHAN
XBAR(IFLAG,ICHAN)=X(ICHAN)
DO 75 JCHAN=ICHAN,NCHAN
INUM=INUM+1
C(IFLAG,INUM)=B(ICHAN,JCHAN)
75 CONTINUE
70 CONTINUE
CALL ROTA (IFLAG,ROT,EIGEN,NCHAN,A,SIGMA)
DO 80 JCLUST=1,NCLUST
DO 85 IRUN=2,MSUB
NSUB=NEXEC(IRUN)
IF (MERGE(JCLUST) .NE. NSUB) GO TO 85
MERGE(JCLUST)=IFLAG
85 CONTINUE
80 CONTINUE
MERGE(JCLUST)=IFLAG
IF(NEXEC(1).EQ.1)GO TO 94
ISW=0
JCHECK=1
DO 90 JCLUST=1,NCLUST
IDUM=MERGE(JCLUST)
91 IF(MERGE(JCLUST).LT.JCHECK)GO TO 90
IF(MERGE(JCLUST).GT.JCHECK)GO TO 92
IF(ISW.EQ.1)GO TO 93
JCHECK=JCHECK+1
IF(JCHECK.EQ.KOUNT)GO TO 94
GO TO 90
92 MERGE(JCLUST)=MERGE(JCLUST)-1
ISW=1
GO TO 91
93 IF (JCHECK .GT. KOUNT) GO TO 94
ISW=0
INUM=0
MPOP(JCHECK)=MPOP(IDUM)
DO 95 ICHAN=1,NCHAN
XBAR(JCHECK,ICHAN)=XBAR(IDUM,ICHAN)
SIGMA(JCHECK,ICHAN)=SIGMA(IDUM,ICHAN)
DO 100 JCHAN=ICHAN,NCHAN
INUM=INUM+1
C(JCHECK,INUM)=C(IDUM,INUM)
ROT(JCHECK,ICHAN,JCHAN)=ROT(IDUM,ICHAN,JCHAN)
ROT(JCHECK,JCHAN,ICHAN)=ROT(IDUM,JCHAN,ICHAN)
100 CONTINUE
95 CONTINUE
DO 96 LCLUST=1,NCLUST

```



```

        IF(MERGE(LCLUST).NE.IDUM)GO TO 96
        MERGE(LCLUST)=JCHECK
96      CONTINUE
        JCHECK=JCHECK+1
90      CONTINUE
        94 KOUNT=KOUNT-NEXEC(1)
10      CONTINUE
11      CONTINUE
        WRITE(LT9) (COM(I),I=1,24)
        WRITE(LT9) ((XBAR(I,J),I=1,KOUNT),J=1,12)
        WRITE(LT9) ((SIGMA(I,J),I=1,KOUNT),J=1,12)
        WRITE(LT9) (((ROT(I,ICHAN,JCHAN),I=1,KOUNT),ICHAN=1,NCHAN),
1 JCHAN=1,NCHAN)
        WRITE(6,1013)
        DO 510 I=1,KOUNT
        WRITE(6,1000) I,(XBAR(I,J),J=1,12)
510     CONTINUE
        WRITE(6,1014)
        DO 511 I=1,KOUNT
        WRITE(6,1000) I,(SIGMA(I,J),J=1,12)
511     CONTINUE
        WRITE(6,1015)
        DO 512 I=1,KOUNT
        WRITE(6,1016) I,((ROT(I,ICHAN,JCHAN),JCHAN=1,12),ICHAN=1,12)
512     CONTINUE
        DO 513 I=1,NCLUST
        IF(MERGE(I).GT.KOUNT)GO TO 514
        WRITE(6,515)I,MERGE(I)
515     FORMAT(1X,7HCLUSTER,14,1X,5HCLASS,14)
513     CONTINUE
514     CONTINUE
        DO 660 I=1,KOUNT
        DO 620 ICHAN=1,NCHAN
        DO 610 JCHAN=1,NCHAN
        B(ICHAN,JCHAN)=ROT(I,JCHAN,ICHAN)/SIGMA(I,ICHAN)
610     CONTINUE
620     CONTINUE
        DO 650 ICHAN=1,NCHAN
        DO 640 KCHAN=1,NCHAN
        SUM=0.0
        DO 630 JCHAN=1,NCHAN
        SUM=SUM+ROT(I,ICHAN,JCHAN)*B(JCHAN,KCHAN)
630     CONTINUE
        A(ICHAN,KCHAN)=SUM
640     CONTINUE
650     CONTINUE
        WRITE(6,600) I
600     FORMAT(1X,13HCLASS ELLIPSE,14)
        WRITE(6,1005) ((A(IA,JA),JA=1,NCHAN),IA=1,NCHAN)
660     CONTINUE
        REWIND LT9
        RETURN
        END

```

```

$IBFTF GETCOR
      SUBROUTINE FETCOR(IFLAG,C,NPOP,NFLG,N
      COMMON /LAB1/XBAR(42,12),SIGMA(42,12),ROT(42,12,12)
      COMMON /LAB2/X(12),ALPHA(49),NSPS,NSCANS,NCHAN,LT9,LT10,LT11,LT12,
1LT13,LT1,IX,IY,
1NSTART,NSTOP,
1NBTLG,MODE,ITYPE,MSFC,I4,NCRE,
1NSKIP,INCX,INCY,NSTX,NSTY
      DIMENSION NPOP(1),C(42,78),NDAT(255)
      DATA NCNT/0/
      INUM=0
      NFLG1=0
      NFLG3=0
      DO 5 ICHAN=1,NCHAN
      XBAR(IFLAG,ICHAN)=0.0
      DO 10 JCHAN=ICHAN,NCHAN
      INUM=INUM+1
      C(IFLAG,INUM)=0.0
10  CONTINUE
5   CONTINUE
      KNT=0
40  CONTINUE
      IF (NCNT .GE. NSCANS) GO TO 70
      NFLG2=0
      READ(LT12)(NDAT(JJ),JJ=1,NSPS)
      NCNT=NCNT+1
      NFLG1=1
      NFLAG2=1
      DO 20 JJ=1,NSPS
      CALL GET7 (X(1),NSPS,0,NCHAN,NSCANO,LT10,IERR,NFLAG2,
1NSTART,NBTLG,MODE,NCRE,ITYPE,MSFC
      IF (NDAT(JJ) .NE. N) GO TO 30
      KNT=KNT+1
      NFLG2=1
      AI=FLOAT(KNT)
      INUM=0
      DO 25 ICHAN=1,NCHAN
      XBAR(IFLAG,ICHAN)=(1.0-1.0/AI)*XBAR(IFLAG,ICHAN)+X(ICHAN)/AI
      DO 26 JCHAN=ICHAN,NCHAN
      INUM=INUM+1
      C(IFLAG,INUM)=(1.0-1.0/AI)*C(IFLAG,INUM)+X(ICHAN)*X(JCHAN)/AI
26  CONTINUE
25  CONTINUE
      GO TO 20
30  CONTINUE
      IF (NFLG3 .EQ. 1) GO TO 20
      IF (NDAT(JJ) .NE. N+1) GOTO 20
      NSAV=NCNT
      NFLG3=1
20  CONTINUE
C  WRITE(6,1000) NCNT,KNT,NSAV,NBCKUP,N,NFLAG2,NFLAG3
1000 FORMAT(1X,7I8)
      IF (NFLG2 .NE. 0) GO TO 40
      IF (NFLG3 .EQ. 0) GO TO 40
      NBCKUP=NCNT-NSAV+1

```

```

CALL BSRECD(LT10,NBCKUP*14,RF)
CALL BSRECD(LT12,NBCKUP,RF)
NCNT=NSAV-1
NPOP(N)=KNT
N=N+1
RETURN
70  CONTINUE
    REWIND LT10
    REWIND LT12
    NFLG=1
    RETURN
    END

```

#### \$IBFTF TRXAM

```

SUBROUTINE AMTRX(IFLAG,XBAR,C,A,NCHAN)
DIMENSION XBAR(42,12),C(42,78)
DOUBLE PRECISION A(12,12)
INUM=0
DO 1 ICHAN=1,NCHAN
DO 2 JCHAN=ICHAN,NCHAN
    INUM=INUM+1
    A(ICHAN,JCHAN)=C(IFLAG,INUM)-XBAR(IFLAG,ICHAN)*XBAR(IFLAG,JCHAN)
    A(JCHAN,ICHAN)=A(ICHAN,JCHAN)
2  CONTINUE
1  CONTINUE
    RETURN
    END

```

#### \$IBFTC ATOR

```

SUBROUTINE ROTA(IFLAG,ROT,EIGEN,NCHAN,A,SIGMA)
DIMENSION ROT(42,12,12)
DIMENSION SIGMA(42,12)
DOUBLE PRECISION A(12,12)
DOUBLE PRECISION EIGEN(12,12)
DO 1 ICHAN=1,NCHAN
    SIGMA(IFLAG,ICHAN)=A(ICHAN,ICHAN)
DO 2 JCHAN=1,NCHAN
    ROT(IFLAG,ICHAN,JCHAN)=EIGEN(JCHAN,ICHAN)
2  CONTINUE
1  CONTINUE
    RETURN
    END

```

#### \$IBFTF KCEHCK

```

SUBROUTINE KCHECK (IFLAG,      ROT,X,SIGMA,ASUM,NCHAN)
DIMENSION ROT(42,12,12),SIGMA(42,12),X(1)
ASUM=0.0
DO 3 ICHAN=1,NCHAN
    SUM=0.0
DO 4 JCHAN=1,NCHAN
    SUM=SUM+ROT(IFLAG,ICHAN,JCHAN)*X(JCHAN)
4  CONTINUE

```

```

3      ASUM=ASUM+SUM*SUM/SIGMA(IFLAG,ICHAN)
      CONTINUE
      RETURN
      END

```

```

$ORIGIN      BRAVO,SYSUT2,REW

```

```

$IBFTC MOD7C

```

```

      SUBROUTINE CLASS(NCLASS,NTEST,NPASS )
      COMMON /LAB1/XBAR(42,12),SIGMA(42,12),ROT(42,12,12)
      COMMON /LAB2/X(12),ALPHA(49),NSPS,NSCANS,NCHAN,LT9,LT10,LT11,LT12,
1LT13,LT1,IX,NDUMMY,
1NSTART,NSTOP,
1NPTLG,MODE,ITYPE,MSFC,14,NCRE,
1NSKIP,INCX,INCY,NSTX,NSTY
      DIMENSION W(12),MTAB(3)
      DIMENSION NDAT(255,3),PRNT(255)
      DIMENSION COM(24)
      EQUIVALENCE(COM(1),NSPS)
      REWIND LT9
      REWIND LT10
      REWIND LT1
      REWIND LT12
      REWIND LT13
      NFLAG1=0
      LT1=1
      IF (NPASS .NE. NTEST) LT1=LT13
      CZECH=NCHAN
      IF (NSKIP .EQ. 0) GO TO 601
      DO 602 I=1,NSKIP
      CALL SKRRIN(LT10,1,NOP)
602  CONTINUE
601  CONTINUE
      READ(LT9) (COM(I),I=1,24)
      READ(LT9) ((XBAR(I,J),I=1,NCLASS),J=1,12)
      READ(LT9) ((SIGMA(I,J),I=1,NCLASS),J=1,12)
      READ(LT9) (((ROT(I,ICHAN,JCHAN),I=1,NCLASS),ICHAN=1,NCHAN),
1JCHAN=1,NCHAN)
      DO 1 I=1,3
1  MTAB(I)=1
      DO 10 IEND=1,NSCANS
      READ(LT12) (NDAT(I,1),I=1,NSPS)
      NFLAG2=1
      DO 20 ISUBN=1,NSPS
      CALL GFT7(X(1),NSPS,0,NCHAN,NSCANO,LT10,IFRR,NFLAG2,
1NSTART,NPTLG,MODE,NCRE,ITYPE,MSFC )
      IF (NDAT(ISUBN,1) .GT. 0 ) NDAT(ISUBN,1)=0
      SMALL=1.75*CZECH
      DO 25 ICLASS=1,NCLASS
      DO 30 ICHAN=1,NCHAN
      W(ICCHAN)=X(ICCHAN)-XBAR(ICCLASS ,ICHAN)
30  CONTINUE
      ASUM=0.0
      DO 35 ICHAN=1,NCHAN
      SUM=0.0

```

```

DO 40 JCHAN=1,NCHAN
SUM=SUM+W(JCHAN)*ROT(ICLASS,ICHAN,JCHAN)
40 CONTINUE
41 ASUM=ASUM+SUM*SUM/SIGMA(ICLASS,ICHAN)
35 CONTINUE
IF (ASUM .GT. SMALL) GO TO 25
SMALL=ASUM
NDAT(ISURN,1)=ICLASS
25 CONTINUE
1016 FORMAT(1X,3I6,F10.2)
20 CONTINUE
WRITE(LT1)(NDAT(I,1),I=1,NSPS)
10 CONTINUE
END FILE LT1
REWIND LT1
REWIND LT12
REWIND LT10
IF (NPASS .NE. NTEST) GO TO 804
DO 610 IZ=1,NSCANS
IY=MTAB(1)
READ(LT1)(NDAT(IA,IY),IA=1,NSPS)
NTEMP=MTAB(1)
MTAB(1)=MTAB(2)
MTAB(2)=MTAB(3)
MTAB(3)=NTEMP
IF (IZ .LT. 3) GO TO 610
DO 620 IA=NSTART,NSTOP
IF (IA .EQ. 1) GO TO 620
IF (IA+1 .GT. NSTOP) GO TO 620
IIY=MTAB(2)
IM=MTAB(1)
IN=MTAB(2)
M=NDAT(IA,IM)
N=NDAT(IA-1,IN)
IF (M .NE. N) GO TO 650
IL=MTAB(3)
L=NDAT(IA,IL)
IF (M .NE. L) GO TO 650
NDAT(IA,IIY)=M
GO TO 620
650 IM=MTAB(1)
M=NDAT(IA-1,IM)
IN=MTAB(3)
N=NDAT(IA-1,IN)
IF (M .NE. N) GO TO 620
L=NDAT(IA+1,IM)
IF (M .NE. L) GO TO 620
NDAT(IA,IIY)=M
620 CONTINUE
IF (IZ .LT. 3) GO TO 610
L=MTAB(1)
WRITE(LT13)(NDAT(I,L),I=1,NSPS)
610 CONTINUE
DO 611 I=2,3
L=MTAB(I)

```

```

        WRITE(LT13) (NDAT(I1,L),IL=1,NSPS)
611  CONTINUE
804  CONTINUE
        REWIND LT1
        REWIND LT9
        REWIND LT13
        REWIND LT10
        LOW=NSTART
        LWER=1
800  CONTINUE
        NHI=LOW+120-1
        NUPPER=LWER+120-1
        IF (NUPPER .GT. NSPS ) NUPPER=NSPS
        IDIF=NUPPER-LWER+1
        WRITE(6,1007)
1007  FORMAT(1H1)
        CALL LABEL7(LOW,NHI,1)
        DO 801 II=1,NSCANS
        READ(LT12) (NDAT(JJ,1),JJ=1,NSPS)
        DO 803 JJ=LWER,NUPPER
        IB=NDAT(JJ,1)
        IRND=IB-(IB-1)/45*45+2
        PRNT(JJ)=ALPHA(IRND)
803  CONTINUE
        CALL PLTBF7(PRNT(LWER),IDIF,NBLK,INCX,INCY,NSTX,NSTY,NCRE,
1  NFLAGX,NFLAG1)
        WRITE(6,1008) II, (PRNT(JJ),JJ=LWER,NUPPER)
1008  FORMAT(4X,I6,1H*,120A1)
801  CONTINUE
        REWIND LT13
        NFLAG1=0
        NFLAGX=0
        LWER=NUPPER+1
        LOW=NHI+1
        IF (NUPPER .LT. NSPS ) GO TO 800
802  CONTINUE
        NSCANS=NSCANS-7
        RETURN
        END

```